


## Specialized RJ45 Cable Glands



- For standard industrial applications using data cables with pre-assembled RJ 45 connectors

- Material: Body, Cap: PA 6 / Seal: CR
- Ingress Protection Rating: IP 68 - 5 Bar, 30 min
- UL Environmental Rating: TYPE 1, 4X acc. to UL 50E
- Flammability: V2 according to UL94
- Operating temperature:
  - Permanent: -20 °C to +100 °C
  - Intermittent: -30 °C to +150 °C



- Cable type: Non armoured, with pre-assembled RJ 45 connector
- Accessories (refers to dedicated page): Locknuts, Washer Gaskets, Dome Plugs

[illegible]

| Outer Thread Size (Male) | Cable Diameter Ø | Outer Thread Length | Spanner Width |             | Outer Ø       | Max. Height   | Light grey RAL 7035  |                 | Grey RAL 7001  |                 | Black RAL 9005  |                 | Pkg     |
|--------------------------|------------------|---------------------|---------------|-------------|---------------|---------------|---------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------------------------|-----------------|---------|
|                          |                  |                     | Cap           | Body        |               |               |                                                                                                         |                 |                                                                                                     |                 |                                                                                                      |                 |         |
|                          | SW Cap           | SW Body             | D             | H           |               |               | Description                                                                                             | Part Number     | Description                                                                                         | Part Number     | Description                                                                                          | Part Number     | per Box |
| mm in                    | mm in            | mm in               | mm in         | mm in       | mm in         |               |                                                                                                         |                 |                                                                                                     |                 |                                                                                                      |                 |         |
| PG 16                    | 6<br>0.236       | 10<br>0.394         | 27<br>1.063   | 27<br>1.063 | 30.9<br>1.217 | 31.9<br>1.256 | EP-RJG-PG16-LGR-A                                                                                       | 1SNG618019R0000 | EP-RJG-PG16-GR-A                                                                                    | 1SNG618020R0000 | EP-RJG-PG16-BL-A                                                                                     | 1SNG618021R0000 | 50      |
| PG 21                    | 6<br>0.236       | 11<br>0.433         | 33<br>1.299   | 33<br>1.299 | 37.2<br>1.465 | 38.4<br>1.512 | EP-RJG-PG16-LGR-B                                                                                       | 1SNG618022R0000 | EP-RJG-PG16-GR-B                                                                                    | 1SNG618023R0000 | EP-RJG-PG16-BL-B                                                                                     | 1SNG618024R0000 | 25      |

[illegible]