









Notes:

- Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25° C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40° C to +85° C
- Material and Finish:
 - Receptacle Housing: Metallized ABS (Nickel Plated); UL94 V-0
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicon, Color: White
 - Cat.5e RJ45 IDC Jack Metal Shell: Copper Alloy, Nickel Plated
 - Cat.5e RJ45 IDC Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
 - Cat.5e RJ45 IDC Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
- Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- IP67 rated when covered or fully mated with the appropriate mating connector
- RoHS compliant

RoHS compliant

Customer:				Tolerance Unless otherwise specified		Autodesk Inventor	Scale: 1.5:1	Dim. in mm
Name	Title	Approval Date		0	PLC ± 0.50		Material: See Notes	
				1	PLC ± 0.38			
				2	PLC ± 0.25		Title: Potted Receptacle Assembly Kit Metallized Plastic Receptacle Housing with Shielded Cat. 5e RJ45 IDC Jack	
				3	PLC ± 0.10			
				ANGLES ± 3°			Drawing No.: 17K1A189	
1 x c	Ä21-0426	27.10.2021	Bub	D-old				
b		Mar/08/2011	Vincent ke				Part No.: 17-10034	
a	original							
Rev	Changes	Date	Name	CONEC®			DIN A3	
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION				DOT NOT ALTER CAD DRAWING BY HAND			Sheet 1/1	