

- Panel Nut: Brass, Finish: Nickel Plated
- Panel Gasket: Silicon, Color: White
- Duplex LC Adaptor Assembly:
- Housing: Mod. PPO , UL94 V-0,
- Color: SM Blue/MM Beige/APC SM Green
- Alignment Sleeves: SM Ceramic/MM Phosphor Bronze
- Dust Cap: PP, Color: Neutral transparent
- Operating Temperature: -40°C to +85°C
- 2. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
- 3. IP67 rated when covered or fully mated with the appropriate mating connector

Description	Part Number
Nickel Plated Die-Cast Duplex LC Single Mode Receptacle + Cover Assembly	17-300380
Nickel Plated Die-Cast Duplex LC Multi Mode Receptacle Cover Assembly	17-300390
Nickel Plated Die-cast Duplex LC APC Single Mode Receptacle Cover Assembly	17-300400

	R TO A THIRD CORPORATION	DRAWING BY HAND	Customer:				Tolerance Unless otherwise specified 0 PLC ± 0.30		<del>\$</del>	Scale: Dim. in mm			
IED OR REPRODUCED SSED ON TO A THIRD	R REPROI D ON TO A N. EC CORPC		Name		Title Approval Date		b 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1'		Autodesk Inventor	Material: See Notes			
	SSEI						2011	Date	Name	Title: IP67 Industria	al Duplay I C		
	SS P.						Draw.	Nov. 09	Vincent Ke		•		
	E S S S S S S S S S S S S S S S S S S S	됬					Appd.	Nov. 09	J. Chaudry	Receptacle + Lov	Cover Assembly Kit		
	Y NO WAY 1	ALTER CAD					Norm			Nickel Plated D	e-Cast Version		
	G MA AND W		1 х с	Ä21-0426	02.11.2021	Bub	D-old			Drawing No. 471/4400	0	DIN	
	AWIN VAY.		Ь	3 x b	Sep/25/201	³ Vincent Ke			Drawing No.: 17K1A302		A3		
7	THIS DRAWING MAY NOT BE COPIED OR RINN NAYWWY, AND MAY NOT BE PASSED ON ARTY WITHOUT WRITTEN PERMISSION.  WHERSHIP AND COPYRIGHT OF CONEC.	TON TO	а	original						Part No.: SEE PART NUMBER TABLE		Sheet	
E≥₹8		18	Day	Changes	Doto	Nome		<b>77   '</b>		I LULLING OLL FAILT IN	OWDER TABLE	1/1	

RoHS compliant