

Han 48B Ex-HSE-M40-reel-HC



Part number	19 36 048 0548
Specification	Han 48B Ex-HSE-M40-reel-HC
HARTING eCatalogue	https://b2b.harting.com/19360480548

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] Ex
Type of hood/housing	Hood
Type	High construction

Version

Locking type	Single locking lever
Size	48 B
Version	Side entry
Cable entry	1x M40
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han [®] Ex inserts!

Technical characteristics

Limiting temperature	-20 ... +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
RoHS	compliant
ELV status	compliant
China RoHS	e



Pushing Performance

Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Commercial data

Packaging size	1
Net weight	1,702 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors