

Technical data sheet

Cap nut cable gland, PG thread, pure white

Item no. 2022575



With Pg connection thread to DIN 40430 robust cap-nut cable gland with large sealing area, as well as strain relief and twist protection for high sealing demands, sealing ring of chloroprene/nitrile rubber, moulded sealing ribs, so no connection thread sealing ring needed, tested to VDE 0619

Protection rating IP 68 at 5 bar for 1 hr.




PA Polyamide

Additional product text 1	Table column D: sealing range to VDE 0619, in which no strain relief is required.
Additional product text 2	Table column D2: Sealing range including strain relief and twist protection to VDE 0619

Master data

Item no.	2022575
Type	V-TEC PG11 RW
Description 1	Cable gland
Dimension	PG11
Colour	Pure white
RAL number	9010
Material	Polyamide
Material symbol	PA
Smallest sales unit (VG)	50 Piece
Weight	0,89 kg/100 pc.

Technical data



Dimension E	25,00 mm
Dimension L min.	22,00 mm
Dimension L max.	29,00 mm
Dimension L1	8,00 mm
Dimension L2	5,00 mm
Dimension L3	17,00 mm
Dimension L4	10,00 mm
WAF	22,00 mm
Version	Straight
Type of seal	Sealing ring
Bend protection	☐
Sealing range D	3,50 - 10,00 mm
Sealing range D	0,20 - 0,39 in
explosion-proof	☐
Flat cable threaded connection	☐
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Thread	PG 11

Technical data sheet

Cap nut cable gland, PG thread, pure white

Item no. 2022575



Technical data

Thread type	PG
Thread length	8,00 mm
Thread increase	1,41 mm
Fibre-glass reinforced	☐
Halogen-free	☒
Installation torque	2,50 Nm
Multiple sealing insert	☐
With locknut	☐
Impact-resistant	☐
Protection rating	IP68
Splittable gland	☐
max. permitted ambient temperature	-20,00 - 65,00 °C
Strain relief and wringing protection D2	4,50 - 10,00 mm
Strain relief option	☒