



NOTES:

1. METALSHELLS: STEEL: min. 320µ" TIN over 80µ" NICKEL
2. INSULATORS: PBTP GF UL 94 V-0; BLACK
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. = CRITICAL DIMENSION
7. CONNECTOR IS PART MARKED: PART NO: CONEC Y/WW

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
NOT ALTER CAD DRAWING BY HAND

				tolerance				scale: 2:1	
								material: SEE NOTES	
				2002	date	name		title: D-SUB COMBINATION FEMALE 25W3S CRIMP STYLE	
				drawn	08.08.	Schmidt			
				appd.	08.08.	Mickenbecker			
				norm	DIN 1652				
				d-old					
						dwg no:		AutoCAD 2000	DIN-A
						13K1A671		3	sh: 1/1
rev.	description	date	name	part no: 3025W3SXX99A30X					