

Polyamide, drain plugs

- Drains condensed water in the housing
- Helps to avoid any potential damage to sensitive electric/electronic equipment in the housing due to condensed water
- Also allows air in the housing to breathe with the surrounding atmosphere
- Material: Body: PA66
- Ingress Protection Rating: IP 56 / IP 66 (Category 2)
- Flammability: V2 according to UL94
- Operating temperature:
 - Permanent: -20 °C to +100 °C
 - Intermittent: -30 °C to +150 °C
- Accessories (refers to dedicated page): Locknuts, Washer Gaskets



Thread Type METRIC acc. to EN 60423

Outer	Oute		Outer Ø Height			ht	Light grey RAL 703	5 🔲	Grey RAL 7001		Black RAL 9005	Pkg	
Thread Size	Thre	ad											
(Male)	Leng	ıgth											
	TL		D I		Н								per
	mm	in	mm	in	mm	in	Description	Part Number	Description Part Number		Description	Part Number	Box
M12x1.5	12	0.5	19	0.7	17	0.7	EP-DRP-M12-LGR-A	1SNG611001R0000	EP-DRP-M12-GR-A	1SNG611002R0000	EP-DRP-M12-BL-A	1SNG611003R0000	100
IIIIZXIIO	112	10.0	10	:0.7	111	:0.7	El Dill Milz Editiv	10110011001110000	El Dill Mile Gilli	TORGOTTOOLITOOO	EI DIW WIIZ DE A	1011001100010000	100

Locknut for polyamide drain plug


Looking for	250 Milet for poryamile of daily plag													
Inner	Inner Spanner Outer Ø Height					ht	Light grey RAL 7035	5	Grey RAL 7001		Black RAL 9005	Pkg		
Thread Size	Thread Size Width													
(Female)	SW													
	Locknut D			Н								per		
	mm	in	mm	in	mm	in	Description	Part Number	Description	Part Number	Description	Part Number	Box	
M12x1.5	18	0.7	19.2	0.8	7	0.3	EP-DRP-M12-LGR-B	1SNG611004R0000	EP-DRP-M12-GR-B	1SNG611005R0000	EP-DRP-M12-BL-B	1SNG611006R0000	100	



Brass, Drain plugs

- Drains condensed water in the housing.
- Helps to avoid any potential damage to sensitive electric/electronic equipment in the housing
- Due to condensed water.
- · Also allows air in the housing to breathe with the surrounding atmosphere
- Material: Body: Brass, Brass Nickel Plated, Stainless Steel Bushing: Bronze / O-Ring: Silicone
- Ingress Protection Rating: IP 68 5 Bar, 30 min / IP66
- Operating temperature: 60 °C to + 85 °C
- Accessories (refers to dedicated page): Locknuts, Washer Gaskets





Thread Type METRIC acc. to EN 60423

	e Outer	Outer Thread Length Spanner Width				Ď	Height				Pkg
(Male)	TL		SW		D	D					
	mm	in	mm	in	mm	in	mm	in	Description	Part Number	per Box
M20x1.5	15	0.591	25	0.984	27.5	1.083	16	0.630	EM-DRP-M20-MET-A	1SNG612001R0000	63
M25x1.5	15	0.591	30	1.181	33	1.299	16	0.630	EM-DRP-M25-MET-A	1SNG612002R0000	35

Thread Type NPT acc. to ANSI ASME B1.20.1

Outer Thread Size Outer Thread Ler		ead Length	Spanner V	Vidth	Outer Ø		Height				Pkg
(Male)	TL		SW	SW		D					
	mm	in	mm	in	mm	in	mm	in	Description	Part Number	per Box
NPT 1/2"	16	0.630	25	0.984	27.5	1.083	16	0.630	EM-DRP-NPT12-MET-A	1SNG612003R0000	63
NPT 3/4"	16	0.630	30	1.181	33	1.299	16	0.630	EM-DRP-NPT34-MET-A	1SNG612004R0000	35

Lo

Locknuts	s For Drain Plugs Bras	ss Nickel Plated Me	Locknuts For Drain Plug Brass Nickel Plated NPSL					
Size			Pkg	Size			Pkg	
	Description	Part Number	per Box		Description	Part Number	per Box	
M20	EM-DRP-M20-MET-B	1SNG612005R0000	63	NPSL 1/2"	EM-DRP-NPT12-MET-B	1SNG612007R0000	63	
M25	EM-DRP-M25-MET-B	1SNG612006R0000	35	NPSL 3/4"	EM-DRP-NPT34-MET-B	1SNG612008R0000	35	

All the main technical data provided are "manufacturer" values

TIOICIO TO OL 11100	totol to the income approval per products														
	1 1														
	Bohs: .av	1			:	:					:		i		
:	I TO I TO : CTANALUS	: :		:		:	:	:	:						
	RoHS USR CNR	1			:	:							:		
<u>:</u>	<u> </u>	:						:							