




Technical specification:


Rated voltage: IEC 60664-1	2PE 4PE 300 V 300V
Overvoltage category: IEC 60664-1	2
Overvoltage: IEC 60664-1	2,7 kV
Current rating: IEC 60664-1	2PE 4PE 16 A 16 A
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: EN 60512-11-10 EN 60512-11-4	-30°C ... +85°C -40°C -40°C ... +85°C
Mating cycles: IEC 60512-9a	>=100
Termination:	crimped

Wire specification:

Temperatur range static	-30°C ... +105°C
flexibel	-10°C ... +105°C


Materials:

Contact:	CuZn, Ni b / Au 0,2 gal.
Contact carrier:	TPU, UL 94 HB
Sealing:	FPM
Socket housing:	CuZn, nickel plated
Grouting:	Polyurethane-resin, UL 94





Contact assignment:

PE	green-yellow
2	brown
3	blue



Contact assignment:

1	black
2	blue
PE	green-yellow
4	brown
5	white



Minimum wall thickness
2,5mm, alternativ panel
cut-out d=18,8

Part no:	Description:	Pos	Length L:	Wire:
41-40117	SAL - 7/8 - FK2PE - 0,5 / 250 - 11	3	0,5m	AWG 14 PVC, UL
41-40118	SAL - 7/8 - FK4PE - 0,5 / 250 - 11	5	0,5m	


DO NOT ALTER CAD DRAWING BY HAND

RoHS & REACH compliant

tolerance of wire: L ≤ 0,5m: L + 20mm
L > 0,5m: L + 4%

general tolerance: 0 ± 0,50mm
0,0 ± 0,25mm
0,00 ± 0,10mm
± ± 1,5°

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND
MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH



dim. in mm

	date	name
drawn	10.06.15	Böckeler
appd.	10.06.15	Mankopf

CONEC®

title:

Female socket 7/8" with wires,
frontmounting, PG11

dwg no:

41K1A570

part no:

see table