




Technical specification/

Technische Daten:


Rated Voltage/ Bemessungsspannung:	63 V AC / 63 V DC
IEC 61076-2-111	
Current rating/ Strombelastbarkeit:	16 A / 40 °C
IEC 61076-2-111	
Insulation resistance/ Isolationswiderstand:	>=100 MΩ
IEC 60512	
Pollution degree/ Verschmutzungsgrad:	3/2
IEC 60664-1	
Degree of protection/ Schutzart:	IP 67, in mated condition/ im verschraubten Zustand
IEC 60529	
Temperature range/ Umgebungstemperatur:	-40 °C ... +105 °C
Mating cycles/ Steckzyklen:	>=100
IEC 60512-9a	

Materials/

Werkstoffe:


Contact/ Kontakt:	CuZn, Ni b / Au 0,2 gal.
Contact carrier/ Kontaktträger:	PA, UL 94 V-0
Sealing/ Dichtung:	FKM

Suitable for reflow soldering
max. 60s / 250°C
geeignet für Reflow Lötprozess
max. 60s / 250°C




Tape & Reel -
parts with suction cap Ø11mm
TR-Artikel mit
Ansaugkappe Ø11mm

Top view
Layout PCB/
Leiterplatte



Part no packing unit Tape & Reel/ Art.-Nr. Verpackungseinheit Rolle:	Part no. packing unit in bulk/ Art.-Nr. Verpackungseinheit lose:	Description/ Beschreibung:	Pos/ Pol:
43-03909TR	43-03909	SAL- 12L - ISO4 / THR	4



dim. in mm

general tolerance/ Allgemeintoleranz:	0 ± 0,50 mm 0,0 ± 0,25 mm 0,00 ± 0,10 mm * ± 1,5°
--	--

	Date/Datum	Name
drawn/ gez.	19.01.2021	Bludau
appd./ gepr.	19.01.2021	Fischer

Male socket M12x1 L-coded THR 4pos.
Flanschstecker M12x1 L-Codiert THR 4pol

Index: b Ä21-0446 09.12.21 ABL

scale/Maßstab:

CONEC®

dwg no /
Z.-nr.:

43K1A5038

DIN-
A4

RoHS & REACH compliant/konform

see table

1 / 1