

Actuator

46-
2818.1CV0.007



<https://testing.eao.com/p/46-2818.1CV0.007>

Your product:



46-2818.1CV0.007 Actuator

FRONT

Front dimension:	Ø 29 mm
Front bezel colour:	Black
Front bezel material:	Plastic
Front form:	round

MOUNTING

Mounting cut-out:	Ø 22.3 mm
Design:	raised

OPERATING-/INDICATION PART

Lever material:	plastic
Lever shape:	short
Lever colour:	Black
Lever bar colour:	White

ELECTRICAL CHARACTERISTICS

Protection class:	II
-------------------	----

MECHANICAL CHARACTERISTIC

Weight:	0.027 kg
Switching positions:	4 positions
Tightening torque:	2 ... 3 Nm (17.7 ... 26.6 Lb-in)

Switching angle:	52°
Mechanical lifetime:	1 Mio. cycles of operation
Switching action:	Maintained - Maintained - Maintained - Maintained

AMBIENT CONDITION


Operating temperature:	– 25 °C ... + 55 °C
Vibration resistance:	5g f= 2...500Hz (EN-IEC 60068-2-6)
Climate resistance:	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Shock resistance:	30g, 18ms (EN-IEC 60068-2-27) 50g, 11ms (EN-IEC 60068-2-27)
IK front protection:	IK06
IP front protection:	IP65

CERTIFICATE


Standards:	CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508
Conformities:	CE
Approbations:	CSA, EAC, UL

OTHER

max. number of switching elements:	8
Housing colour:	Black
Short Description:	Actuator, Ø 22.3 mm, Ø 29 mm, non illuminative, Black, short, round, Black, Plastic, Maintained - Maintained - Maintained - Maintained, IP65, IK06
Housing material:	Plastic
Dimension drawings:	



Switching positions:



Mounting cut-outs:

