

Actuator

46-
2W28.3CP0.001



<https://testing.eao.com/p/46-2W28.3CP0.001>

Your product:



46-2W28.3CP0.001 Actuator

FRONT

Front dimension:	Ø 30 mm
Front bezel material:	Metal
Front bezel colour:	Silver
Front form:	round

MOUNTING

Mounting cut-out:	Ø 22.3 mm
Design:	raised

OPERATING-/INDICATION PART

Lever bar colour:	White
Lever colour:	Red
Lever material:	plastic
Lever shape:	short

ELECTRICAL CHARACTERISTICS

Protection class:	II
-------------------	----

MECHANICAL CHARACTERISTIC

Tightening torque:	2 ... 3 Nm (17.7 ... 26.6 Lb-in)
Mechanical lifetime:	1 Mio. cycles of operation
Switching angle:	90°

Switching positions: 2 positions

Weight: 0.038 kg

Switching action: Maintained - Maintained

AMBIENT CONDITION

IK front protection: IK03

IP front protection: IP65

Operating temperature: – 25 °C ... + 55 °C

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
50g, 11ms (EN-IEC 60068-2-27)

CERTIFICATE

Conformities: CE

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER


Short Description: Actuator, Ø 22.3 mm, Ø 30 mm, illuminative, Red, short, round, Silver, Metal, Maintained - Maintained, IP65, IK03

Housing colour: Black

max. number of switching elements: 2

Housing material: Plastic

Switching positions:



Dimension drawings:

