



**475-TR10-1/475-TR40-1**

**1/4" Bits Torx® Tamper Resistant**  
**25 mm, Box 5 Pcs**

## PRODUCT DETAILS

- For Torx® tamper-resistant screws with safety pin
- 1/4" hex drive
- For universal use
- High performance alloy steel
- Sandblasted finish
- Available in plastic box of 5 pieces
- DIN 3126 and ISO 1173 Style C 6.3



## PRODUCT ATTRIBUTES

| Product           |  |  |  |  |  |
|-------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>475-TR10-1</b> | 5                                                                                   | T 10                                                                                | 2.74 mm                                                                              | 25 mm                                                                                 | 35 g                                                                                  |
| <b>475-TR15-1</b> | 5                                                                                   | T 15                                                                                | 3.27 mm                                                                              | 25 mm                                                                                 | 35 g                                                                                  |
| <b>475-TR20-1</b> | 5                                                                                   | T 20                                                                                | 3.86 mm                                                                              | 25 mm                                                                                 | 35 g                                                                                  |
| <b>475-TR25-1</b> | 5                                                                                   | T 25                                                                                | 4.43 mm                                                                              | 25 mm                                                                                 | 35 g                                                                                  |
| <b>475-TR27-1</b> | 5                                                                                   | T 27                                                                                | 4.99 mm                                                                              | 25 mm                                                                                 | 35 g                                                                                  |
| <b>475-TR30-1</b> | 5                                                                                   | T 30                                                                                | 5.52 mm                                                                              | 25 mm                                                                                 | 40 g                                                                                  |
| <b>475-TR40-1</b> | 5                                                                                   | T 40                                                                                | 6.65 mm                                                                              | 25 mm                                                                                 | 50 g                                                                                  |