


Actuator

51-
381.F22DF



<https://eao.com/p/51-381.F22DF>

Your product:



51-381.F22DF Actuator

FRONT

Front dimension: 18 mm x 18 mm

MOUNTING

Mounting cut-out: 21 mm x 21 mm

Design: flush

ELECTRICAL CHARACTERISTICS

Thermal current I_{th}: 5 A, according to EN / IEC 60947-5-1

Protection class: II

Electric strength: 2500 VAC, 50 Hz, 1 min. between all terminals and earth, according to IEC 61058-1, part 15

Switching voltage and switching current: 250 VAC, 5 A ($\cos\phi$ 0.75)

Contacts: 2 NC / 2 NO

Electrostatic discharge (ESD): ≤ 15 KV

MECHANICAL CHARACTERISTIC

Switching action: Maintained - Rest (a) - Maintained

Terminal: Plug-in terminal, 2.8 x 0.5 mm

Mechanical lifetime: 50 000 cycles of operation

Switching system: Self-cleaning, double-break snap action switching system, 2 normally closed and 2 normally open contact per element.

Switching system: Snap-action switching element

Weight: 0.027 kg

Switching positions:	3 positions
Switching angle:	90° left / 90° right
Tightening torque:	Fixing nut max. 0.5 Nm
Contact material:	Gold
Wire cross section:	Max. wire cross-section 2 wires with 1 mm Max. wire cross-section of stranded cable 2 x 0.75 mm ²


AMBIENT CONDITION

Storage temperature:	– 40 °C ... + 85 °C
Operating temperature:	– 25 °C ... + 55 °C
IP front protection:	IP65, according to DIN EN 60529


CERTIFICATE

Conformities:	CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 30 / EU (EMC), 2014 / 35 / EU (LVD)
Approbations:	CB (IEC 61058-1), CQC, CSA, DNV, ENEC (EN 61058-1), UL


OTHER

max. number of switching elements:	1
Short Description:	Actuator, 21 mm x 21 mm, 18 mm x 18 mm, 2 NC / 2 NO, Maintained - Rest (a) - Maintained, Plug-in terminal, 2.8 x 0.5 mm, IP65, according to DIN EN 60529
Housing colour:	Black
Hints:	Standard lock: DOM 311
Wiring diagrams:	

Mounting cut-outs:



Switching positions:



Dimension drawings:

