

# Diamond Mounted Point Set, Cylindrical and Tapered to Point, 2 Pcs.



**For grinding ceramics, glass, tiles, non-ferrous metals**



## Properties

- 2 diamond mounted points, Ø 8 mm cylindrical, Ø 3–8 mm tapered to point for deburring and regrinding bores and chamfering edges
- diamond coated for high hardness, dimensional stability and service life when used on ceramics, glass, tiles and non-ferrous metals
- 3 mm shaft for easy mounting in drills, cordless screwdrivers, flexible shafts and miniature rotary tools

## Technical data

|                                  |   |
|----------------------------------|---|
| Shaft diameter                   | 3 mm  |
| Direction of rotation            | Clockwise rotation                              |
| Material/coating property        | Diamond coated                                  |
| Additional product specification | Ø 8 mm cylindrical<br>Ø 3–8 mm tapered to point |

## Scope of delivery


- 1 diamond mounted point, Ø 8 mm, cylindrical
- 1 diamond mounted point, Ø 3–8 mm, tapered to point

# Diamond Mounted Point Set, Cylindrical and Tapered to Point, 2 Pcs.



## Compatible with tool

Power Drill

| Article number | Contents | Parts in set | Grinding stone height | Speed of rotation, max. | EAN-Code  |
|----------------|----------|--------------|-----------------------|-------------------------|---|
| 5989000        | 1        | 2 pcs.       | 10 mm                 | 25,000 RPM              | <br>4 006885 598904<br>4006885598904 |