## **SIEMENS**

Data sheet 5SD7581-3



Overvoltage protection for Ethernet interfaces up to 10 Gbit/s, including POE

| Model   |  |
|---|--|
| product brand name  | SENTRON  |
| product designation   | Surge protection device                                  |
| design of the product   | Surge arrester 5SD7 for measuring and control technology |
| design of the product explosion-proof design  | No   |
| General technical data  |  |
| break time  |  |
| <ul> <li>between L and N for symmetrical circuit</li> </ul>   | 1 ns   |
| <ul> <li>between L or N and PE for symmetrical circuit</li> </ul>   | 100 ns   |
| insertion loss for symmetrical circuit  |  |
| with characteristic wave impedance 100 ohm up to 5 MHz typical  | 1 dB   |
| power pulse current at (10/1000) µs   | 40 A   |
| capacity between switched connecting terminals  |  |
| <ul> <li>for symmetrical circuit</li> </ul>   | 0.012 nF   |
| for asymmetrical circuit  | 1 pF   |
| protection level  |  |
| <ul> <li>with pulse curve shape C2 at (10 kV/5 kA) to signal<br/>ground according to IEC 61643-21</li> </ul>  | 700 V  |
| overvoltage category  |  |
| Voltage   |  |
| continuous operating voltage  |  |
| at DC maximum   | 3.3 V  |
| residual voltage between L and L  |  |
| for rated discharge current for symmetrical circuit   | 15 V   |
| voltage limitation of the output voltage  |  |
| <ul> <li>between L and L at rate of voltage rise 1 kV/µs for spike<br/>or statistical distribution in relation to hazard level for<br/>symmetrical circuit</li> </ul>   | 9 V  |
| <ul> <li>between L and PE for asymmetrical circuit at rate of<br/>voltage rise 1 kV/µs for spike or statistical distribution in<br/>relation to hazard level</li> </ul> | 700 V  |
| Supply voltage  |  |
| operating voltage   |  |
| rated value maximum   | 3.3 V  |
| Protection class  |  |
| protection class IP   | IP20   |
| Product details   |  |
| product component remote signaling contact  | No   |
| Product function  |  |
| product function surge arrester monitoring  | No   |
| Connections   |  |

| type of electrical connection        | RJ4  | RJ45          |              |                             |
|--------------------------------------|------|---------------|--------------|-----------------------------|
| Mechanical Design                    |      |               |              |                             |
| height                               | 25 m | nm            |              |                             |
| width                                | 102  | mm            |              |                             |
| depth                                | 65 m | nm            |              |                             |
| net weight                           | 289  | g             |              |                             |
| material of the enclosure            | ZnA  | ZnAl4Cu1      |              |                             |
| Environmental conditions             |      |               |              |                             |
| ambient temperature during operation |      |               |              |                             |
| • minimum                            | 40 ° | С             |              |                             |
| • maximum                            | 85 ° | C             |              |                             |
| Approvals Certificates               |      |               |              |                             |
| General Product Approval             |      | other         |              | Environment                 |
| Confirmation  EG-Kenf.               | EAC  | Miscellaneous | Confirmation | Environmental Confirmations |

## Environment

**Environmental Confirmations** 

## Further information

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SD7581-3

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) <a href="https://support.industry.siemens.com/cs/ww/en/ps/5SD7581-3">https://support.industry.siemens.com/cs/ww/en/ps/5SD7581-3</a>

EG-Konf.

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5SD7581-3

**CAx-Online-Generator** 

**Tender specifications** 

http://www.siemens.com/specifications

| last modified: | 3/12/2024 🗗 |
|----------------|-------------|