

5SND 0500N330300

HiPak IGBT Module

$$V_{CE} = 3300 \text{ V}$$

$$I_C = 500 \text{ A}$$

Ultra low-loss, rugged SPT+ chip-set
 Smooth switching SPT+ chip-set for good EMC
 AlSiC base-plate for high power cycling capability
 AlN substrate for low thermal resistance
 2 switches in one package



Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	max	Unit
Collector-emitter voltage	V_{CES}	$V_{GE} = 0 \text{ V}$, $T_{vj} \geq 25 \text{ }^{\circ}\text{C}$		3300	V
DC collector current	I_C	$T_C = 100 \text{ }^{\circ}\text{C}$, $T_{vj} = 150 \text{ }^{\circ}\text{C}$		500	A
Peak collector current	I_{CM}	$t_p = 1 \text{ ms}$		1000	A
Gate-emitter voltage	V_{GES}		-20	20	V
Total power dissipation	P_{tot}	$T_C = 25 \text{ }^{\circ}\text{C}$, $T_{vj} = 150 \text{ }^{\circ}\text{C}$, per switch		4800	W
DC forward current	I_F			500	A
Peak forward current	I_{FRM}	$t_p = 1 \text{ ms}$		1000	A
Surge current	I_{FSM}	$V_R = 0 \text{ V}$, $T_{vj} = 150 \text{ }^{\circ}\text{C}$, $t_p = 10 \text{ ms}$, half-sinewave		4500	A
IGBT short circuit SOA	t_{psc}	$V_{CC} = 2500 \text{ V}$, $V_{CEM \text{ CHIP}} \leq 3300 \text{ V}$ $V_{GE} \leq 15 \text{ V}$, $T_{vj} \leq 150 \text{ }^{\circ}\text{C}$		10	μs
Isolation voltage	V_{isol}	1 min, $f = 50 \text{ Hz}$		6000	V
Junction temperature	T_{vj}			175	$^{\circ}\text{C}$
Junction operating temperature	$T_{vj(op)}$		-50	150	$^{\circ}\text{C}$
Case temperature	T_C		-50	150	$^{\circ}\text{C}$
Storage temperature	T_{stg}		-50	125	$^{\circ}\text{C}$
Mounting torques ²⁾	M_s	Base- heatsink, M6 screws	4	6	Nm
	M_{t1}	Main terminals, M8 screws	8	10	
	M_{t2}	Auxiliary terminals, M4 screws	2	3	

¹⁾ Maximum rated values indicate limits beyond which damage to the device may occur per IEC 60747

²⁾ for detailed mounting instructions refer to ABB Document No. 5SYA 2039

IGBT characteristic values ³⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector (-emitter) breakdown voltage	V _{(BR)CES}	V _{GE} = 0 V, I _C = 10 mA, T _{vj} = 25 °C	3300			V
Collector-emitter ⁴⁾ saturation voltage	V _{CE sat}	I _C = 500 A, V _{GE} = 15 V	T _{vj} = 25 °C	2.5	2.9	V
			T _{vj} = 125 °C	3.1		V
			T _{vj} = 150 °C	3.25	3.4	V
Collector cut-off current	I _{CES}	V _{CE} = 3300 V, V _{GE} = 0 V	T _{vj} = 25 °C		0.3	mA
			T _{vj} = 125 °C	6.5	13	mA
			T _{vj} = 150 °C	30		mA
Gate leakage current	I _{GES}	V _{CE} = 0 V, V _{GE} = ± 20 V, T _{vj} = 125 °C	-500		500	nA
Gate-emitter threshold voltage	V _{GE(th)}	I _C = 80 mA, V _{CE} = V _{GE} , T _{vj} = 25 °C	5		7	V
Gate charge	Q _G	I _C = 500 A, V _{CE} = 1800 V, V _{GE} = -15 V ..15 V		3.7		μC
Input capacitance	C _{ies}	V _{CE} = 25 V, V _{GE} = 0 V, f = 1 MHz, T _{vj} = 25 °C		50		nF
Output capacitance	C _{oes}			4.2		nF
Reverse transfer capacitance	C _{res}			1.28		nF
Internal gate resistance	R _{Gint}	per switch		1.8		Ω
Turn-on delay time	t _{d(on)}	V _{CC} = 1800 V, I _C = 500 A, R _G = 3.9 Ω, V _{GE} = ±15 V, L _σ = 125 nH, inductive load	T _{vj} = 25 °C	380		ns
			T _{vj} = 125 °C	400		ns
			T _{vj} = 150 °C	400		ns
Rise time	t _r		T _{vj} = 25 °C	135		ns
			T _{vj} = 125 °C	140		ns
			T _{vj} = 150 °C	145		ns
Turn-off delay time	t _{d(off)}		T _{vj} = 25 °C	1250		ns
			T _{vj} = 125 °C	1450		ns
			T _{vj} = 150 °C	1460		ns
Fall time	t _f		T _{vj} = 25 °C	255		ns
			T _{vj} = 125 °C	340		ns
			T _{vj} = 150 °C	360		ns
Turn-on switching energy	E _{on}	V _{CC} = 1800 V, I _C = 500 A, R _G = 3.9 Ω, V _{GE} = ±15 V, L _σ = 125 nH, inductive load	T _{vj} = 25 °C	660		mJ
		T _{vj} = 125 °C	860		mJ	
		T _{vj} = 150 °C	960		mJ	
Turn-off switching energy	E _{off}	V _{CC} = 1800 V, I _C = 500 A, R _G = 3.9 Ω, V _{GE} = ±15 V, L _σ = 125 nH, inductive load	T _{vj} = 25 °C	620		mJ
		T _{vj} = 125 °C	850		mJ	
		T _{vj} = 150 °C	920		mJ	
Short circuit current	I _{SC}	t _{psc} ≤ 10 μs, V _{GE} = 15 V, V _{CC} = 2500 V, V _{CEM CHIP} ≤ 3300 V	T _{vj} = 150 °C	2170		A

³⁾ Characteristic values according to IEC 60747 - 9

⁴⁾ Collector-emitter saturation voltage is given at chip level

Diode characteristic values ⁵⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward voltage ⁶⁾	V _F	I _F = 500 A	T _{vj} = 25 °C	2.05		V
			T _{vj} = 125 °C	2.25		V
			T _{vj} = 150 °C	2.20		V
Peak reverse recovery current	I _{RM}	V _{CC} = 1800 V, I _F = 500 A, V _{GE} = ±15 V, R _G = 3.9 Ω, di/dt = 3.8 kA/μs L _σ = 125 nH, inductive load	T _{vj} = 25 °C	690		A
			T _{vj} = 125 °C	810		A
			T _{vj} = 150 °C	830		A
Recovered charge	Q _r		T _{vj} = 25 °C	360		μC
			T _{vj} = 125 °C	585		μC
			T _{vj} = 150 °C	680		μC
Reverse recovery time	t _{rr}		T _{vj} = 25 °C	930		ns
			T _{vj} = 125 °C	1250		ns
			T _{vj} = 150 °C	1410		ns
Reverse recovery energy	E _{rec}		T _{vj} = 25 °C	400		mJ
			T _{vj} = 125 °C	680		mJ
			T _{vj} = 150 °C	800		mJ

⁵⁾ Characteristic values according to IEC 60747 - 2

⁶⁾ Forward voltage is given at chip level

Package properties ⁷⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
IGBT thermal resistance junction to case	$R_{th(j-c)IGBT}$	per switch			0.026	K/W
Diode thermal resistance junction to case	$R_{th(j-c)DIODE}$				0.05	K/W
IGBT thermal resistance ²⁾ case to heatsink	$R_{th(c-s)IGBT}$	IGBT per switch, λ grease = $1\text{W}/\text{m} \times \text{K}$		0.024		K/W
Diode thermal resistance ²⁾ case to heatsink	$R_{th(c-s)DIODE}$	Diode per switch, λ grease = $1\text{W}/\text{m} \times \text{K}$		0.048		K/W
Partial discharge extinction voltage	V_e	$f = 50 \text{ Hz}$, $Q_{PD} \leq 10 \text{ pC}$ (acc. To IEC 61287)	3500			V
Comparative tracking index	CTI		600			
Module stray inductance	$L_{\sigma CE}$	per switch		24		nH
Resistance, terminal-chip	$R_{CC'+EE'}$	per switch	$T_C = 25 \text{ }^{\circ}\text{C}$	0.180		m Ω
			$T_C = 125 \text{ }^{\circ}\text{C}$	0.245		
			$T_C = 150 \text{ }^{\circ}\text{C}$	0.260		


²⁾ For detailed mounting instructions refer to ABB Document No. 5SYA 2039

Mechanical properties ⁷⁾


Parameter	Symbol	Conditions	min	typ	max	Unit
Dimensions	L x W x H	Typical	130 x 160 x 38			mm
Clearance distance in air	d_a	according to IEC 60664-1 and EN 50124-1	Term. to base:	19		mm
			Term. to term:	19		
Surface creepage distance	d_s	according to IEC 60664-1 and EN 50124-1	Term. to base:	28.2		mm
			Term. to term:	28.2		
Mass	m			850		g

⁷⁾ Package and mechanical properties according to IEC 60747 - 15

Electrical configuration



Outline drawing ²⁾



Note: all dimensions are shown in millimeters

²⁾ For detailed mounting instructions refer to ABB Document No. 5SYA 2039

This is an electrostatic sensitive device, please observe the international standard IEC 60747-1, chap. IX.
This product has been designed and qualified for Industrial Level.




Fig. 1 Typical on-state characteristics, chip level




Fig. 2 Typical transfer characteristics, chip level




Fig. 3 Typical output characteristics, chip level




Fig. 4 Typical output characteristics, chip level




Fig. 5 Typical switching energies per pulse vs. collector current




Fig. 6 Typical switching energies per pulse vs. gate resistor




Fig. 7 Typical switching times vs. collector current




Fig. 8 Typical switching times vs. gate resistor




Fig. 9 Typical capacitances vs. collector-emitter voltage




Fig. 10 Typical gate charge characteristics




Fig. 11 Turn-off safe operating area (RBSOA)




Fig. 12 Typical reverse recovery characteristics vs. forward current




Fig. 13 Typical reverse recovery characteristics vs. di/dt




Fig. 14 Typical diode forward characteristics chip level




Fig. 15 Safe operating area diode (SOA)




Fig. 16 Thermal impedance vs. time

Analytical function for transient thermal impedance:

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

	i	1	2	3	4	5
IGBT	$R_i(K/kW)$	17.56	4.12	1.922	1.896	
	$\tau_i(ms)$	207.4	30.1	7.55	1.57	
DIODE	$R_i(K/kW)$	34.2	8.56	3.84	3.84	
	$\tau_i(ms)$	203.6	30.1	7.53	1.57	

Related documents:

5SYA 2042 Failure rates of HiPak modules due to cosmic rays
 5SYA 2043 Load - cycle capability of HiPaks
 5SYA 2045 Thermal runaway during blocking
 5SYA 2053 Applying IGBT
 5SYA 2058 Surge currents for IGBT diodes
 5SYA 2093 Thermal design and temperature ratings of IGBT modules
 5SYA 2098 Paralleling of IGBT modules
 5SZK 9111 Specification of environmental class for HiPak Storage
 5SZK 9112 Specification of environmental class for HiPak Transportation
 5SZK 9113 Specification of environmental class for HiPak Operation (Industry)
 5SZK 9120 Specification of environmental class for HiPak

ABB Switzerland Ltd.
 Semiconductors
 Fabrikstrasse 3
 CH-5600 Lenzburg
 Switzerland

Phone: +41 58 586 1419
 Fax: +41 58 586 1306
 E-Mail: abbsem@ch.abb.com
 Internet: www.abb.com/semiconductors

We reserve the right to make technical changes or to modify the contents of this document without prior notice.

We reserve all rights in this document and the information contained therein. Any reproduction or utilization of this document or parts thereof for commercial purposes without our prior written consent is forbidden.

Any liability for use of our products contrary to the instructions in this document is excluded.