

Terminal block enclosure

RK 4/18 K-L



RK 4/18 K-L

Terminal block enclosure

CUSTOMIZABLE

Productnumber: 61591201

Dimensions: 180 x 110 x 90 mm

Terminal block enclosure, polystyrene, light grey, similar to RAL 7035, incl. 8 attachment bushes M20, seal range 8 - 13.5 mm, IP54, 2 attachment bushes M25, seal range 9 - 18.5 mm, IP54, 1 attachment bush M32, seal range 13 - 23 mm, IP54

without terminals, with NS 35

IP54
IP66

4²

IK07



400V
AC



To industrial product:

<https://www.spelsberg.com/p/63591201>

Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	400 V
Type of protection:	IP54/IP66
Max. conductor cross section:	4 mm²
Protection class:	II

Dimensions

Width:	180 mm
Length:	110 mm
Height:	90 mm

Material characteristics

suitable for exterior use:	no
----------------------------	----

Material characteristics

Halogen free:	yes
Industry quality:	no

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

HBA - Mounting material

ASS-gro - External hinge set

VSG - Padlock kit

KS M20 - Combi set

KS M25 - Combi set

KS M25-gro - Combi set

KS M32 - Combi set

TK ABL - External fixing lugs kit