

666N

Click-type torque wrenches with reversible ratchets, for right-hand tightening, torque accuracy: $\pm 3\%$



UNI EN ISO 6789

- Scale increased by 60% for improved visibility and setting accuracy
- Torque adjusting speed increased by 40%
- Handle and lens materials resistant to all chemical substances used in automotive sector, industry and aviation
- Red colour of o-ring indicates that wrench is unlocked and torque can be adjusted
- When not in use, set torque to lowest value of torque wrench range



	art.	Nm	Kgfm	lbf.ft	■	D mm	A mm	L mm	g	Incremento
006660002	666N/2	5÷25	0,5÷2,5	4÷18	1/4	25	29	220	300	2,0 Nm
006660003	666N/2X	5÷25	0,5÷2,5	4÷18	3/8	25	29	220	300	2,0 Nm
006660005	666N/5	10÷50	1÷5	7÷37	3/8	30	33	325	660	0,2 Nm
006660010	666N/10	20÷100	2÷10	15÷75	3/8	30	33	367	730	0,2 Nm
006660011	666N/10X	20÷100	2÷10	15÷75	1/2	30	37	367	800	0,5 Nm
006660020	666N/20	40÷200	4÷20	30÷150	1/2	40	43	465	1010	1,0 Nm
006660030	666N/30	60÷300	6÷30	50÷220	1/2	40	43	581	1380	1,0 Nm