



SIWAREX WP321 WEIGHING ELECTRONIC (1 CHANNEL) FOR STRAIN GAUGE LOAD CELLS / FULL BRIDGES (1-4 mV/V) FOR SIMATIC ET200SP, FITS to BU-TYPE A0, RS485- INTERFACE FOR CONNECTION OF SIWATOOL OR A REMOTE DISPLAY

General information	
Product type designation	TM SIWAREX WP321 ST
HW functional status	FS04
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Adjustment of measuring range	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V14 or higher
• STEP 7 configurable/integrated from version	From STEP 7 V5.4 and higher
• PROFIBUS from GSD version/GSD revision	GSD Revision 5
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes
Input current	
Current consumption, max.	100 mA
Power	
Power available from the backplane bus	70 mW
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
• Inputs	16 byte
• Outputs	16 byte
Encoder	
Connection of signal encoders	
• For strain gauges (full bridges) with 4-conductor connection	Yes

For strain gauges (full bridges) with 6-conductor connection	Yes
Resistance of full bridge, min.	40 Ω; when using SIWAREX IS: 50 ohm for 7MH4710-5BA; 105 ohm when using 7MH4710-5CA
Resistance of full bridge, max.	4 100 Ω
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Error limit according to DIN 1319-1	0.05 %; of full-scale value
Temperature coefficient, zero point	≤ ±0.1 μV/K
Temperature coefficient, span	≤ ±5 ppm/K
1. Interface	
Interface types	
RS 485	Yes; 390 Ω, 220 Ω, 390 Ω connectable termination
Interface types	
RS 485	
Transmission rate, max.	115.2 kbit/s
Cable length, max.	1 000 m; ≤ 115 kbps, shielded cable
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Diagnostic alarm
Substitute values connectable	No
Alarms	
Diagnostic alarm	Yes; Parameterizable
Hardware interrupt	Yes; Parameterizable
Diagnoses	
Monitoring the supply voltage	Yes
Wire-break	Yes
Short-circuit	Yes
Diagnostics indication LED	
ERROR LED	Yes; green/red DIAG LED
Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
Integrated Functions	
Load cell	
Non-automatic weighing instrument	NAWI
permissible input signal per verification interval, min.	0.5 μV/d (d=e)
Sampling rate	600 Hz
Resolution of input signal	±500 000 parts pro mV/V
Common mode voltage, min.	0.25 V
Common mode voltage, max.	4.75 V
input resistance of signal line, typ.	4 MΩ
input resistance of sense line, typ.	2 MΩ
Cable length, max.	500 m; when using the SIWAREX 7MH4702-8AG cable
Measuring functions	
Measuring range	
— -1 mV/V to +1 mV/V	Yes; corresponds to a resolution of ±500 000 parts
— -2 mV/V to +2 mV/V	Yes; corresponds to a resolution of ±1 000 000 parts
— -4 mV/V to +4 mV/V	Yes; corresponds to a resolution of ±2 000 000 parts
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
horizontal installation, min.	-25 °C
horizontal installation, max.	60 °C
vertical installation, min.	-25 °C
vertical installation, max.	50 °C
Altitude during operation relating to sea level	
Installation altitude above sea level, max.	5 000 m; more than 2 000 m above sea level, the ambient temperature is reduced by -1 °C per 100 m
Ambient air temperature-barometric pressure-	1 080 ... 795 hPa (-1 000 ... 5 000 m above sea level)

altitude	
Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	15 mm
Height	57 mm
Depth	72 mm
Weights	
Weight, approx.	31 g
last modified:	2/12/2021 