

PRODUCT-DETAILS

## **TY25M-2**

## CABLE TIE 50LB 7IN RED NYLON



| General Information   |  |
|-----------------------|--|
| Extended Product Type | TY25M-2  |
| Product ID            | 7TAG009270R0011  |
| EAN                   | 5414363062516  |
| Catalog Description   | CABLE TIE 50LB 7IN RED NYLON   |
| Long Description      | High Performance Cable Tie for Indoor applications, Red Color Nylon 6.6, Length of 186mm (7.3 Inches) for Bundle Diameter up to 48mm (1.89 Inches), Width of 4.9mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Military Specified (MIL-SPEC MS3367-1-2), Bulk Pack |

| Ordering                |               |
|-------------------------|---------------|
| E-Number (Finland)      | 1381483       |
| EAN                     | 5414363062516 |
| UPC                     | 786210844855  |
| Country of Origin       | Hungary (HU)  |
| Customs Tariff Number   | 3926909985    |
| Selling Unit of Measure | each          |

| Dimensions          |          |
|---------------------|----------|
| Product Net Width   | 0.184 in |
|                     | 4.67 mm  |
| Product Net Depth / | 7.31 in  |

Length 185.67 mm

| Container Information          |                   |
|--------------------------------|-------------------|
| Package Level 1 Units          | 1000 piece        |
| Package Level 2 Units          | 10000 piece       |
| Package Level 2 Width          | 13.4 in<br>340 mm |
| Package Level 2 Height         | 10.1 in<br>257 mm |
| Package Level 2 Depth / Length | 21.1 in<br>536 mm |

| Technical UL/CSA       |     |
|------------------------|-----|
| Flammability According | V-2 |
| to UL94                |     |

| Additional Information |  |
|------------------------|--|
| Brand / Label          | Ty-Rap   |
| Bundle Diameter        | 0.12 to 1.89 in<br>3 to 48 mm  |
| Color                  | Red  |
| Effective Date         | 19680313   |
| Lock Type              | Stainless Steel Barb   |
| Material               | Nylon/Polyamide 6.6  |
| Product Name           | NYLON CABLE TIES AND ACCESSORIES   |
| Product Type           | High Performance   |
| Special Functions      | Low profile head is designed to prevent snags on uneven surfaces and<br>easier to pull through bulkheads. Non-magnetic stainless steel locking<br>device insures both maximum strength and the right tightness every time. |
| Standards              | UL E49405  |
| Tensile Strength       | 50 lb  |
|                        | 222 N  |
| Thickness              | 0.05 in  |
|                        | 1.3 mm   |

| Certificates and Declarations (Document Number) |                 |
|---|-----------------|
| Data Sheet, Technical<br>Information            | TDS000518       |
| Declaration of<br>Conformity - CE               | 9AKK107492A9841 |
| Instructions and<br>Manuals                     | TY25M-2         |

| Classifications                       |                           |
|---------------------------------------|---------------------------|
| ETIM 6                                | EC000046 - Cable tie      |
| ETIM 7                                | EC000046 - Cable tie      |
| ETIM 8                                | EC000046 - Cable tie      |
| UNSPSC                                | 39121703                  |
| WEEE Category                         | Product Not in WEEE Scope |
| IDEA Granular Category<br>Code (IGCC) | 5034 >> Cable ties        |

TY25M-2 3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

