

PRODUCT-DETAILS

TY28M-2 CABLE TIE 50LB 14IN RED NYLON



| General Information | |
|-----------------------|-----------------|
| Extended Product Type | TY28M-2 |
| Product ID | 7TAG009270R0021 |
| EAN | 5414363063513 |

Catalog Description CABLE TIE 50LB 14IN RED NYLON

Long Description

High Performance Cable Tie for Indoor Applications, Red Color Nylon 6.6, Length of 361mm (14.2 Inches) for Bundle Diameter up to 102mm (4.02 Inches), Width of 4.9mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of 60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Military Specified (MIL -SPEC MS3367-2-2), Bulk Pack

| Ordering | | |
|-------------------------|---------------|--|
| EAN | 5414363063513 | |
| UPC | 786210845081 | |
| Country of Origin | Hungary (HU) | |
| Customs Tariff Number | 3926909985 | |
| Selling Unit of Measure | each | |

| Dimensions | |
|----------------------------|---------------------|
| Product Net Width | 0.19 in 4.82 mm |
| Product Net Depth / Length | 14.2 in 360.5 mm |

| Container Information | |
|--|--|
| Package Level 1 Units | 1000 piece |
| Package Level 1 Width | 14 in |
| Desired Level 1 Death / | 356 mm |
| Package Level 1 Depth / Length | 20 in 508 mm |
| Package Level 2 Units | 5000 piece |
| Package Level 2 Width | 12.1 in |
| Dookogo Lovol 2 Hoight | 307 mm |
| Package Level 2 Height | 9.9 in 251 mm |
| Package Level 2 Depth / | 20 in |
| Length | 508 mm |
| Technical UL/CSA | |
| Flammability According to | V-2 |
| UL94 | <u> </u> |
| | |
| Additional Information | |
| Brand / Label | Ту-Rар |
| Bundle Diameter | 0.12 to 4.02 in 3 to 102 mm |
| Color | Red |
| Effective Date | 19680313 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | NYLON CABLE TIES AND ACCESSORIES |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards | UL E49405 |
| Tensile Strength | 50 lb |
| Thickness | 222 N 0.05 in |
| HIICKHESS | 1.3 mm |
| Certificates and Declarations (Do | cument Number) |
| Data Sheet, Technical | TDS000518 |
| Information | 120000010 |
| Declaration of Conformity | 9AKK107492A9841 |
| - CE Instructions and Manuals | TY28M-2 |
| Instructions and Manuals | 112011-2 |
| | |
| Classifications | |
| | EC000046 - Cable tie |
| ETIM 6 | |
| ETIM 6 ETIM 7 | EC000046 - Cable tie |
| ETIM 6 ETIM 7 ETIM 8 | EC000046 - Cable tie EC000046 - Cable tie EC000046 - Cable tie 39121703 |
| Classifications ETIM 6 ETIM 7 ETIM 8 UNSPSC WEEE Category | EC000046 - Cable tie EC000046 - Cable tie |

TY28M-2 3

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$

