

PRODUCT-DETAILS

TY46MDX

CABLE TIE 50LB 7 UV BLK ID 1.17X1



General Information

Extended Product Type	TY46MDX
Product ID	7TAG009510R0030
EAN	5414363064978
Catalog Description	CABLE TIE 50LB 7 UV BLK ID 1.17X1
Long Description	Identification Cable Tie - Double Strap Configuration, Natural Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 185mm (7.3 Inches), Width of 4.8mm (0.19 Inches), Thickness of 1.3mm (0.05 Inches), Tensile Strength Rating of 220 Newtons (49 Pounds), Marking Pad Size of 30.5mm (1.2Inches) x 28mm (1.1 Inches)

Ordering

EAN	5414363064978
UPC	786210899565
Country of Origin	United States (US)
Customs Tariff Number	3926909985
Selling Unit of Measure	each

Dimensions

Product Net Width	0.19 in 4.81 mm
Product Net Depth / Length	7.25 in 184.15 mm

Container Information

Package Level 1 Units	500 piece
Package Level 2 Units	1000 piece
Package Level 2 Width	10.5 in 267 mm
Package Level 2 Height	8.1 in 206 mm
Package Level 2 Depth / Length	12.8 in 325 mm

Technical UL/CSA

Flammability According to UL94	V-2
--------------------------------	-----

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	1 to 1.75 in 25.4 to 44.4 mm
Color	Natural
Effective Date	19921117
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	Identification
Tensile Strength	49 lb 220 N
Thickness	0.05 in 1.3 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000576
Instructions and Manuals	TY46MDX

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5040 >> I.D. Ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

