

PRODUCT-DETAILS

TY33MX

CABLE TIE 18LB 4IN BLK NYL MTG HOLE



| General Information | |
|-----------------------|--|
| Extended Product Type | TY33MX |
| Product ID | 7TAG009520R0048 |
| EAN | 5414363064213 |
| Catalog Description | CABLE TIE 18LB 4IN BLK NYL MTG HOLE |
| Long Description | Integrated Mounting Hole Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 91mm (3.6 Inches), Width of 2.5mm (0.1 Inches), Thickness of 1mm (0.04 Inches), Tensile Strength Rating of 80 Newtons (18 pounds), #4 Screw for Mounting, Bulk Pack |

| Ordering | |
|-------------------------|--------------------|
| EAN | 5414363064213 |
| UPC | 786210830896 |
| Country of Origin | United States (US) |
| Customs Tariff Number | 3926909985 |
| Selling Unit of Measure | each |
| | |

| Dimensions | |
|-------------------------------|--------------------|
| Product Net Width | 0.09 in 2.31 mm |
| Product Net Depth / Lenath | 4 in 101.61 mm |

| Container Information | |
|--------------------------------------|--|
| Package Level 1 Units | 1000 piece |
| Package Level 1 Width | 4.9 i |
| 5 | 124 mr |
| Package Level 1 Height | 3.6 ii 91 mn |
| Package Level 1 Depth / Length | 8.2 ii 208 mn |
| Package Level 2 Units | 10000 piece |
| Package Level 2 Width | 7.5 ii |
| Package Level 2 Height | 191 mn 9 ii |
| Package Level 2 Depth / | 229 mn 10.3 ir |
| Length | |
| Technical UL/CSA | |
| Flammability According to UL94 | V-2 |
| | |
| Additional Information | |
| Brand / Label | Ty-Raj |
| Bundle Diameter | 0.08 to 0.63 i 2 to 16 mr |
| Color | Blac |
| Effective Date | 1975032 |
| Lock Type | Stainless Steel Barl |
| Material | Nylon/Polyamide 6. |
| Product Name | NYLON CABLE TIES AND ACCESSORIES |
| Product Type | Integrated Mounting Holi |
| RoHS Date Special Functions | 9AKK107991A806 Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures |
| Tensile Strength | both maximum strength and the right tightness every time 18 It 80 N |
| Thickness | 0.04 ir 1 mn |
| | |
| Certificates and Declarations (D | • |
| Data Sheet, Technical Information | TDS00057 |
| Instructions and Manuals | TY33M) |
| REACH Declaration | 9AKK107992A399 |
| RoHS Information | 9AKK107991A8069 |
| Oleverities at the | |
| Classifications | |
| ETIM 6 | EC000046 - Cable ti |
| ETIM 7 | EC000046 - Cable ti |
| ETIM 8 | EC000046 - Cable ti |
| UNSPSC | 3912170 |
| WEEE Category | Product Not in WEEE Scop |

5044 >> Mounted Head Ties

IDEA Granular Category Code (IGCC) TY33MX 3

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$

