

PRODUCT-DETAILS

## TY23MFR

## CABLE TIE 18LB 4IN WHI NYL FLM RTD

General Information	
Extended Product Type	TY23MFR
Product ID	7TAG009570R0002
EAN	5414363061823
Catalog Description	CABLE TIE 18LB 4IN WHI NYL FLM RTD
Long Description	Cable Tie, Flame Retardant White Nylon 6.6, Temperature Range of -20 to 65 Degrees Celsius (-4 to 149 F) for Indoor Applications, Length of 92mm (3.6 Inches), Width of 2.3mm (0.09 Inch), Thickness of 1mm (0.04 Inch), Maximum Bundle Diameter 16mm (0.63 Inch), Tensile Strength Rating of 80 Newtons (18 Pounds)

Ordering	
EAN	5414363061823
UPC	786210801056
Country of Origin	United States (US) Hungary (HU)
Customs Tariff Number	3926909985
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1000 piece
Package Level 1 Width	10 in 254 mm
Package Level 1 Depth / Length	12 in 305 mm

Package Level 2 Units	10000 piece
Package Level 2 Width	9.2 in
•	234 mm
Package Level 2 Height	10.5 in
	267 mm
Package Level 2 Depth /	10.5 in
Length	267 mm

## Technical UL/CSA Flammability According V-0 to UL94

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.06 to 0.63 in 1.5 to 16 mm
Color	White
Effective Date	19780721
Lock Type	Stainless Steel Barb
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	Flame Retardant
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	18 lb 80 N
Thickness	0.04 in 1 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	TDS000478
Instructions and Manuals	TY23MFR

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

## Categories

TY23MFR 3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$