

PRODUCT-DETAILS

TYP25MX

CABLE TIE 30LB 7IN UV BLACK PP

General Information	
Extended Product Type	TYP25MX
Product ID	7TAG009600R0001
EAN	5414363067689
Catalog Description	CABLE TIE 30LB 7IN UV BLACK PP
Long Description	Cable Tie, Black Polypropylene for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 186mm (7.3 Inches), Width of 4.8mm (0.19 Inches), Thickness of 1.3mm (0.05 Inches), Tensile Strength Rating of 180 Newtons (40 Pounds)

5414363067689
786210825304
United States (US)
3926909985
each

Dimensions	
Product Net Width	0.186 in 4.72 mm
Product Net Depth / Length	7.015 in 178.18 mm

Container Information	
Package Level 1 Units	1000 piece
Package Level 2 Units	10000 piece
Package Level 2 Width	13.5 in 343 mm
Package Level 2 Height	9.7 in 246 mm
Package Level 2 Depth / Length	21.1 in 536 mm

Technical UL/CSA

Flammability According	НВ
to III 94	

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.12 to 1.77 in 3 to 45 mm
Color	Black
Effective Date	19820203
Lock Type	Stainless Steel Barb
Material	Polypropylene
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	40 lb 180 N
Thickness	0.05 in 1.3 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	TDS000575
Instructions and Manuals	TYP25MX

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

TYP25MX 3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$