

PRODUCT-DETAILS

## TY125-40X CABLE TIE 40LB 5.5IN UV BLACK NYLON



General Information	
Extended Product Type	TY125-40X
Product ID	7TAG054360R0141
EAN	5414363060680
Catalog Description	CABLE TIE 40LB 5.5IN UV BLACK NYLON
Long Description	"Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 143mm, Width of 3.6mm, Thickness of 1.17mm, Tensile Strength Rating of 180 Newtons, 1000 Pack

	143mm, Width of 3.6mm, Thickness of 1.1/mm , Tensile Strength Rating of 180 Newtons, 1000 Pack"
Ordering	
EAN	5414363060680
UPC	786210898568
Country of Origin	Hungary (HU) United States (US)
Customs Tariff Number	3926909990
Selling Unit of Measure	each
Dimensions	
	0.44
Product Net Width	0.14 in 3.556 mm
Product Net Depth /	5.57 in 141.48 mm
Product Net Depth /	5.

Container Information	
Package Level 1 Units	1000 piece
Package Level 1 Width	9 in 229 mm
Package Level 1 Height	2.6 mm
Package Level 1 Depth / Length	12.7 in 323 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	13.2 in
	335 mm
Package Level 2 Height	10.5 in 267 mm
Package Level 2 Depth / Length	17.1 in 434 mm
Technical UL/CSA	
Flammability According to	V-2
UL94	
Additional Information	
Brand / Label	Ty-Fast
Bundle Diameter	32 mm 1.26 in
Color	Black
Effective Date	19921030
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6 Weather Resistant
Product Name	PLASTIC CABLE TIE
Product Type	General Purpose
Special Functions	"The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool"
Standards	UL E49405
Tensile Strength	180 N 40 lb
Thickness	1.2 mm 0.047 in
Certificates and Declarations (Doc	
Data Sheet, Technical Information	TDS000751
Declaration of Conformity - CE	9AKK107492A9843
Instructions and Manuals	TY125-40X
REACH Declaration	9AKK108466A3876
RoHS Information	9AKK108466A3872
Classifications	
	EC000046 - Cable tie
ETIM 6	
ETIM 6 ETIM 7	EC000046 - Cable tie EC000046 - Cable tie EC000046 - Cable tie
ETIM 6 ETIM 7 ETIM 8	EC000046 - Cable tie
Classifications  ETIM 6  ETIM 7  ETIM 8  UNSPSC  WEEE Category	EC000046 - Cable tie EC000046 - Cable tie

TY125-40X 3

## Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$ 

