



PRODUCT-DETAILS

TY400-120X

CABLE TIE 120LB 15IN UV BLACK NYLON



General Information

Extended Product Type	TY400-120X
Product ID	7TAG054360R0307
EAN	5414363064527
Catalog Description	CABLE TIE 120LB 15IN UV BLACK NYLON
Long Description	"Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 374mm, Width of 7.6mm, Thickness of 1.9mm , Tensile Strength Rating of 540 Newtons, 500 Pack"

Ordering

E-Number (Finland)	1370016
EAN	5414363064527
UPC	786210898278
Country of Origin	Hungary (HU) United States (US) Mexico (MX)
Customs Tariff Number	3926909985
Selling Unit of Measure	each

Dimensions

Product Net Width	0.299 in 7.595 mm
-------------------	----------------------

Product Net Depth /	14.76 in
Length	374.65 mm

Container Information

Package Level 1 Units	500 piece
Package Level 1 Width	15 in 381 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	21 in 533 mm
Package Level 2 Units	2500 piece
Package Level 2 Width	13 in 330 mm
Package Level 2 Height	13.5 in 343 mm
Package Level 2 Depth / Length	18.25 in 464 mm

Technical UL/CSA

Flammability According to UL94	V-2
--------------------------------	-----

Additional Information

Brand / Label	Ty-Fast
Bundle Diameter	103.1 mm 4.059 in
Color	Black
Effective Date	19921219
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6 Weather Resistant
Product Name	PLASTIC CABLE TIE
Product Type	General Purpose
Special Functions	"The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool"
Standards	UL E49405
Tensile Strength	540 N 121 lb
Thickness	1.9 mm 0.075 in

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000751
Declaration of Conformity - CE	9AKK107492A9843
Instructions and Manuals	TY400-120X
REACH Declaration	9AKK108466A3876
RoHS Information	9AKK108466A3872

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

