



PRODUCT-DETAILS

L-11-50MH-0-C

CABLE TIE 50LB 11IN BLK NYL MTG HOL



General Information

Extended Product Type	L-11-50MH-0-C
Product ID	7TAG054670R0001
EAN	5414363025450
Catalog Description	CABLE TIE 50LB 11IN BLK NYL MTG HOL
Long Description	Integrated Mounting Hole Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet for Indoor and Outdoor Applications, Length of 309mm (12.1 Inches), Width of 4.8mm (0.19 Inch), Thickness of 1.3mm (0.05 Inch), Tensile Strength Rating of 222 Newtons (50 Pounds), #10 Screw for Mounting, 100 Pack

Ordering

EAN	5414363025450
UPC	728494910604
Country of Origin	Thailand (TH)
Customs Tariff Number	3926909985
Selling Unit of Measure	each

Dimensions

Product Net Width	0.19 in 4.8 mm
Product Net Depth / Length	12.1 in 309 mm

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	2 in 51 mm
Package Level 1 Depth / Length	15 in 381 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	13.3 in 338 mm
Package Level 2 Height	10.7 in 272 mm
Package Level 2 Depth / Length	16.5 in 419 mm

Technical UL/CSA

Flammability According to UL94	V-2
--------------------------------	-----

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.0625 to 3 in 1.59 to 76.2 mm
Color	Black
Effective Date	19960215
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6 Weather Resistant
Product Name	NYLON CABLE TIE
Product Type	Intergrated Mounting Hole
Standards	UL E49405
Tensile Strength	50 lb 222 N
Thickness	0.05 in 1.3 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000443
Instructions and Manuals	L-11-50MH-0-C

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

