



PRODUCT-DETAILS

TYC527MX

CBL TIE 85LB 13IN UV BLACK NYLON 12



General Information

| | |
|-----------------------|---|
| Extended Product Type | TYC527MX |
| Product ID | 7TCG009580R0007 |
| EAN | 5414363126775 |
| Catalog Description | CBL TIE 85LB 13IN UV BLACK NYLON 12 |
| Long Description | Cable Tie, Black Polyamide (Nylon 12) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 343mm (13.5 Inches), Width of 7.4mm (0.29 Inches), Thickness of 1.6mm (0.05 Inches), Tensile Strength Rating of 380 Newtons (85 Pounds) |

Ordering

| | |
|-------------------------|------------------------------------|
| EAN | 5414363126775 |
| UPC | 786210927831 |
| Country of Origin | Hungary (HU) United States (US) |
| Customs Tariff Number | 3926909990 |
| Selling Unit of Measure | each |

Dimensions

| | |
|----------------------------|----------------------|
| Product Net Width | 0.295 in 7.49 mm |
| Product Net Depth / Length | 13.37 in 339.6 mm |

Container Information

| | |
|--------------------------------|-------------------|
| Package Level 1 Units | 50 piece |
| Package Level 1 Width | 5 in 127 mm |
| Package Level 1 Height | 1 in 25 mm |
| Package Level 1 Depth / Length | 18 in 457 mm |
| Package Level 2 Units | 2000 piece |
| Package Level 2 Width | 10.2 in 259 mm |
| Package Level 2 Height | 9.1 in 231 mm |
| Package Level 2 Depth / Length | 19.7 in 500 mm |

Technical UL/CSA

| | |
|--------------------------------|-----|
| Flammability According to UL94 | V-2 |
|--------------------------------|-----|

Additional Information

| | |
|-------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | 0.19 to 4 in 4.8 to 102 mm |
| Color | Black |
| Effective Date | 20040209 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 12 |
| Product Name | OTHER PLASTICS ITEMS |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Tensile Strength | 90 lb 400 N |
| Thickness | 0.06 in 1.5 mm |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------|
| Data Sheet, Technical Information | TDS000575 |
| Instructions and Manuals | TYC527MX |

Classifications

| | |
|------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

