

Illuminated pushbutton Ø 16 mm silver contact

82-4152.1123



<https://eao.com/p/82-4152.1123>

Your product:



82-4152.1123

Illuminated pushbutton Ø
16 mm silver contact

FRONT

Front bezel shape:	flush
Front bezel material:	Stainless steel

MOUNTING

Mounting cut-out:	Ø 16 mm
-------------------	---------

OPERATING-/INDICATION PART

Lens illumination:	illuminative
Lens colour:	Silver
Lens shape:	flush
Illumination colour:	Blue
Lens optics:	opaque
Shape of illumination:	Ring
Lens material:	Stainless steel

ELECTRICAL CHARACTERISTICS

Operating voltage:	12 V AC/DC
Rated insulation voltage U_i :	250 V
Contacts:	1 C
Rated Operational Voltage U_e :	250 VAC
Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground
Thermal current I_{th} :	5 A

Electrical lifetime:	50 000 cycles of operation		
Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15 Voltage 24 VAC 35 VAC 110 VAC 220 VAC Switch rating DC service categorie DC-13 (Silver contacts) Voltage 24 VDC 35 VDC 110 VDC 220 VDC		
			Current 1 A 1 A (M12 versio 1 A 0.5 A Current 0.7 A 0.5 A (M12 vers 0.2 A 0.1 A
	according to UL 508 (Silver contacts) cosφ 0,75 ... 0,8 Voltage 120 VAC 240 VAC 24 VAC		
		Current	5 A 3 A 1 A
Pollution degree:	2, according to EN IEC 60947-1		

MECHANICAL CHARACTERISTIC

Operating force:	4 N ... 7 N
Operating Travel:	ca. 3 mm
Mechanical lifetime:	1 Mio. cycles of operation
Switching action:	Momentary
Tightening torque:	0.5 ... 0.6 Nm, Screw terminal 0.1 Nm
Switching system:	Snap-action switching element
Contact material:	Silver
Terminal:	Screw terminal
Weight:	0.018 kg

AMBIENT CONDITION

Operating temperature:	– 30 °C ... + 70 °C
Storage temperature:	– 40 °C ... + 80 °C
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

CERTIFICATE

Conformities:

CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

Approbations:

CB, CCC, C UL, UL

OTHER


Kind of illumination:

Single-LED


Short Description:

Illuminated pushbutton Ø 16 mm silver contact, Momentary, 12 V AC/DC, 1 C, Screw terminal, Stainless steel, Blue, Silver


Mounting cut-outs:




Wiring diagrams:



Component layouts:



Dimension drawings:



A = Solder terminal
B = Screw terminal