

Pushbutton Ø 19 mm silver contact

82-5151.1000.B001



<https://eao.com/p/82-5151.1000.B001>

Your product:



82-5151.1000.B001
Pushbutton Ø 19 mm silver contact

FRONT

Front bezel shape:	flush
Front bezel material:	Stainless steel

MOUNTING

Mounting cut-out:	Ø 19 mm
--------------------------	---------

OPERATING-/INDICATION PART

Lens material:	Stainless steel
Lens shape:	flush
Lens illumination:	non illuminative
Lens colour:	Silver
Lens optics:	opaque

ELECTRICAL CHARACTERISTICS

Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15	Current 1 A 1 A (M12 versio 1 A 0.5 A
	Voltage 24 VAC 35 VAC 110 VAC 220 VAC	Current 0.7 A 0.5 A (M12 vers 0.2 A 0.1 A
	Switch rating DC service categorie DC-13 (Silver contacts) Voltage 24 VDC 35 VDC 110 VDC 220 VDC	

according to UL 508 (Silver contacts)	
$\cos\phi$ 0,75 ... 0,8	
Voltage	Current
120 VAC	5 A
240 VAC	3 A
24 VAC	1 A

Electrical lifetime:	50 000 cycles of operation
Rated insulation voltage Ui:	250 V
Thermal current Ith:	5 A
Electric strength:	1500 VAC, 50 Hz 1 minute between live terminals and ground
Rated Operational Voltage Ue:	250 VAC
Pollution degree:	2, according to EN IEC 60947-1

MECHANICAL CHARATERISTIC

Operating force:	4 N ... 7 N
Weight:	0.018 kg
Tightening torque:	0.5 ... 0.6 Nm
Operating Travel:	ca. 3 mm
Switching system:	Snap-action switching element
Mechanical lifetime:	1 Mio. cycles of operation
Switching action:	Momentary
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Contact material:	Silver

AMBIENT CONDITION

Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Operating temperature:	- 30 °C ... + 70 °C
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Storage temperature:	- 40 °C ... + 80 °C

CERTIFICATE

Approbations:	CB, CCC, C UL, UL
Conformities:	CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

OTHER


Short Description:

Pushbutton Ø 19 mm silver contact, Momentary, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, ON/OFF, Silver


Symbol:

ON/OFF


Wiring diagrams:




Component layouts:



Mounting cut-outs:



Dimension drawings:



A = Solder terminal
B = Screw terminal