

Illuminated pushbutton Ø 19 mm silver contact

82-5151.2123.B001



<https://eao.com/p/82-5151.2123.B001>

Your product:



82-5151.2123.B001
Illuminated pushbutton Ø
19 mm silver contact

FRONT

Front bezel material: Stainless steel
Front bezel shape: flush

MOUNTING

Mounting cut-out: Ø 19 mm

OPERATING-/INDICATION PART

Illumination colour: Blue
Lens colour: Silver
Lens illumination: illuminative
Lens shape: flush
Shape of illumination: Ring
Lens material: Stainless steel
Lens optics: opaque

ELECTRICAL CHARACTERISTICS

Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15	Current 1 A 1 A (M12 versio 1 A 0.5 A
Voltage	24 VAC 35 VAC 110 VAC 220 VAC	Current 1 A 1 A (M12 versio 1 A 0.5 A
Switch rating DC service categorie DC-13 (Silver contacts)		
Voltage	24 VDC 35 VDC 110 VDC 220 VDC	Current 0.7 A 0.5 A (M12 vers 0.2 A 0.1 A

according to UL 508 (Silver contacts)

$\cos\phi$ 0,75 ... 0,8

Voltage	Current
120 VAC	5 A
240 VAC	3 A
24 VAC	1 A

Thermal current Ith:	5 A
Operating voltage:	12 V AC/DC
Rated insulation voltage Ui:	250 V
Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground
Contacts:	1 C
Electrical lifetime:	50 000 cycles of operation
Rated Operational Voltage Ue:	250 VAC
Pollution degree:	2, according to EN IEC 60947-1

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	500 000 cycles of operation
Operating Travel:	ca. 3 mm
Contact material:	Silver
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Switching system:	Snap-action switching element
Operating force:	4 N ... 7 N
Tightening torque:	0.5 ... 0.6 Nm
Switching action:	Maintained
Weight:	0.018 kg

AMBIENT CONDITION

Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Storage temperature:	- 40 °C ... + 80 °C
Operating temperature:	- 30 °C ... + 70 °C

CERTIFICATE

Approbations: CB, CCC, C UL, UL

Conformities: CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)


OTHER

Kind of illumination: Single-LED


Short Description: Illuminated pushbutton Ø 19 mm silver contact, Maintained, 12 V AC/DC, 1 C, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, Blue, ON/OFF, Silver

Symbol: ON/OFF


Component layouts:




Mounting cut-outs:



Wiring diagrams:



Dimension drawings:



A = Solder terminal
B = Screw terminal