

Pushbutton Ø 19 mm silver contact

82-5161.2000.B002



<https://eao.com/p/82-5161.2000.B002>

Your product:



82-5161.2000.B002
Pushbutton Ø 19 mm silver contact

FRONT

Front bezel shape:	flush
Front bezel material:	Stainless steel

MOUNTING

Mounting cut-out:	Ø 19 mm
--------------------------	---------

OPERATING-/INDICATION PART

Lens shape:	raised
Lens optics:	opaque
Lens material:	Stainless steel
Lens colour:	Silver
Lens illumination:	non illuminative

ELECTRICAL CHARACTERISTICS

Rated insulation voltage Ui:	250 V
Contacts:	1 C
Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground
Rated Operational Voltage Ue:	250 VAC
Thermal current Ith:	5 A
Electrical lifetime:	50 000 cycles of operation
Pollution degree:	2, according to EN IEC 60947-1
Switching voltage and switching current:	

according to IEC 60947-5-1 (Silver contacts)
Service categorie AC-15

Voltage	Current
24 VAC	1 A
35 VAC	1 A (M12 version)
110 VAC	1 A
220 VAC	0.5 A
Switch rating DC service categorie DC-13 (Silver contacts)	
Voltage	Current
24 VDC	0.7 A
35 VDC	0.5 A (M12 version)
110 VDC	0.2 A
220 VDC	0.1 A

according to UL 508 (Silver contacts)
 $\cos\phi$ 0,75 ... 0,8

Voltage	Current
120 VAC	5 A
240 VAC	3 A
24 VAC	1 A

MECHANICAL CHARACTERISTIC

Switching system:	Snap-action switching element
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Weight:	0.02 kg
Operating force:	4 N ... 7 N
Contact material:	Silver
Mechanical lifetime:	500 000 cycles of operation
Tightening torque:	0.5 ... 0.6 Nm
Switching action:	Maintained
Operating Travel:	ca. 3 mm

AMBIENT CONDITION

Operating temperature:	- 30 °C ... + 70 °C
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Storage temperature:	- 40 °C ... + 80 °C

CERTIFICATE

Approbations:	CB, CCC, C UL, UL
----------------------	-------------------

Conformities:


CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

OTHER


Symbol: Standby

Short Description: Pushbutton Ø 19 mm silver contact, Maintained, 1 C, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, Standby, Silver


Mounting cut-outs:




Wiring diagrams:



Component layouts:



Dimension drawings:



A = Solder terminal
B = Screw terminal