

Illuminated pushbutton Ø 19 mm silver contact

82-5551.2114



<https://eao.com/p/82-5551.2114>

Your product:



82-5551.2114
Illuminated pushbutton Ø
19 mm silver contact

FRONT

Front bezel shape:	flush
Front bezel material:	Aluminium

MOUNTING

Mounting cut-out:	Ø 19 mm
--------------------------	---------

OPERATING-/INDICATION PART

Lens material:	Aluminium
Lens colour:	Nature
Lens shape:	flush
Lens illumination:	illuminative
Lens optics:	opaque
Shape of illumination:	Ring
Illumination colour:	Red

ELECTRICAL CHARACTERISTICS

Pollution degree:	2, according to EN IEC 60947-1
Rated insulation voltage Ui:	250 V
Electrical lifetime:	50 000 cycles of operation
Operating voltage:	24 V DC
Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground
Thermal current Ith:	5 A

Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15
Voltage	Current
24 VAC	1 A
35 VAC	1 A (M12 versio
110 VAC	1 A
220 VAC	0.5 A
Switch rating DC service categorie DC-13 (Silver contacts)	
Voltage	Current
24 VDC	0.7 A
35 VDC	0.5 A (M12 vers
110 VDC	0.2 A
220 VDC	0.1 A

Contacts:	1 C
Rated Operational Voltage Ue:	250 VAC

MECHANICAL CHARATERISTIC

Weight:	0.018 kg
Contact material:	Silver
Switching system:	Snap-action switching element
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Switching action:	Maintained
Operating force:	4 N ... 7 N
Tightening torque:	0.5 ... 0.6 Nm
Operating Travel:	ca. 3 mm
Mechanical lifetime:	500 000 cycles of operation

AMBIENT CONDITION

Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Operating temperature:	- 30 °C ... + 70 °C
Storage temperature:	- 40 °C ... + 80 °C
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27

CERTIFICATE

Conformities:

CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

Approbations:

CB, CCC, C UL, UL

OTHER


Short Description:

Illuminated pushbutton Ø 19 mm silver contact, Maintained, 24 V DC, 1 C, Soldering terminal, 2.8 x 0.5 mm, Aluminium, Red, Nature

Kind of illumination:


Single-LED

Dimension drawings:




A = Solder terminal
B = Screw terminal

Component layouts:



Mounting cut-outs:



Wiring diagrams:

