

Illuminated pushbutton Ø 22 mm stainless steel 304, with
symbol

82-6151.1A14.B006



<https://eao.com/p/82-6151.1A14.B006>

Your product:



82-6151.1A14.B006

Illuminated pushbutton Ø 22 mm
stainless steel 304, with symbol

FRONT

Front bezel material: Stainless steel

MOUNTING

Mounting cut-out: Ø 22 mm

OPERATING-/INDICATION PART

Lens material: Plastic metalised

Illumination colour: Red

Lens shape: flush

Shape of illumination: Symbol

Lens illumination: illuminative

Lens colour: Silver

Lens optics: opaque

ELECTRICAL CHARACTERISTICS

Operating voltage: 24 V DC

Contacts: 1 C

Electrical lifetime: 50 000 cycles of operation

Rated insulation voltage U_i : 250 V

Rated Operational Voltage U_e : 250 VAC

Thermal current I_{th} : 5 A

Pollution degree: 2, according to EN IEC 60947-1

Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground		
Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15 Voltage 24 VAC 35 VAC 110 VAC 220 VAC Switch rating DC service categorie DC-13 (Silver contacts) Voltage 24 VDC 35 VDC 110 VDC 220 VDC		
		Current	1 A
			1 A (M12 versio
			1 A
			0.5 A
		Current	0.7 A
			0.5 A (M12 vers
			0.2 A
			0.1 A
	according to UL 508 (Silver contacts) cosφ 0,75 ... 0,8 Voltage 120 VAC 240 VAC 24 VAC		
		Current	5 A
			3 A
			1 A

MECHANICAL CHARACTERISTIC

Operating force:	4 N ... 7 N
Switching action:	Momentary
Operating Travel:	ca. 3 mm
Contact material:	Silver
Mechanical lifetime:	1 Mio. cycles of operation
Tightening torque:	0.5 ... 0.6 Nm
Switching system:	Snap-action switching element
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Weight:	0.025 kg

AMBIENT CONDITION

Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Storage temperature:	– 40 °C ... + 80 °C
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Operating temperature:	– 30 °C ... + 70 °C

CERTIFICATE

Conformities: CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

Approbations: CB, CCC, C UL, UL


OTHER

Symbol: Door open


Short Description: Illuminated pushbutton Ø 22 mm stainless steel 304, with symbol, Momentary, 24 V DC, 1 C, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, Red, Door open, Silver

Kind of illumination: Single-LED


Wiring diagrams:



Dimension drawings:



Component layouts:



Mounting cut-outs:

