

Illuminated pushbutton Ø 22 mm silver contact

82-6152.2123.B001



<https://eao.com/p/82-6152.2123.B001>

Your product:



82-6152.2123.B001
Illuminated pushbutton Ø
22 mm silver contact

FRONT

Front bezel shape: flush
Front bezel material: Stainless steel

MOUNTING

Mounting cut-out: Ø 22 mm

OPERATING-/INDICATION PART

Illumination colour: Blue
Lens shape: flush
Lens optics: opaque
Lens colour: Silver
Lens material: Stainless steel
Lens illumination: illuminative
Shape of illumination: Ring

ELECTRICAL CHARACTERISTICS

Rated Operational Voltage Ue: 250 VAC
Rated insulation voltage Ui: 250 V
Switching voltage and switching current:

according to IEC 60947-5-1 (Silver contacts)

Service categorie AC-15

Voltage	Current
24 VAC	1 A
35 VAC	1 A (M12 version)
110 VAC	1 A
220 VAC	0.5 A

Switch rating DC service categorie DC-13 (Silver contacts)

Voltage	Current
24 VDC	0.7 A
35 VDC	0.5 A (M12 version)
110 VDC	0.2 A
220 VDC	0.1 A

according to UL 508 (Silver contacts)

$\cos\phi$ 0,75 ... 0,8

Voltage	Current
120 VAC	5 A
240 VAC	3 A
24 VAC	1 A

Operating voltage: 12 V AC/DC

Pollution degree: 2, according to EN IEC 60947-1

Contacts: 1 C

Electrical lifetime: 50 000 cycles of operation

Thermal current I_{th} : 5 A

Electric strength: 1500 VAC, 50 Hz 1 minute between life terminals and ground

MECHANICAL CHARACTERISTIC

Operating Travel: ca. 3 mm

Operating force: 4 N ... 7 N

Tightening torque: 0.5 ... 0.6 Nm, Screw terminal 0.1 Nm

Weight: 0.018 kg

Contact material: Silver

Terminal: Screw terminal

Switching system: Snap-action switching element

Mechanical lifetime: 500 000 cycles of operation

Switching action: Maintained

AMBIENT CONDITION

Climate resistance: Damp heat, 21 days according to IEC 60512-11

Shock resistance: Max. 500 m / s² as per IEC 60068-2-27

Operating temperature:

– 30 °C ... + 70 °C

Storage temperature:

– 40 °C ... + 80 °C

Vibration resistance:

10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

CERTIFICATE

Conformities:

CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

Approbations:

CB, CCC, C UL, UL

OTHER

Kind of illumination:

Single-LED


Short Description:

Illuminated pushbutton Ø 22 mm silver contact, Maintained, 12 V AC/DC, 1 C, Screw terminal, Stainless steel, Blue, ON/OFF, Silver


Symbol:

ON/OFF


Mounting cut-outs:



Component layouts:



Dimension drawings:



A = Solder terminal
B = Screw terminal

Wiring diagrams:

