

Illuminated pushbutton Ø 22 mm silver contact

82-6551.2124



<https://eao.com/p/82-6551.2124>

Your product:



82-6551.2124
Illuminated pushbutton Ø
22 mm silver contact

FRONT

Front bezel material:	Aluminium
Front bezel shape:	flush

MOUNTING

Mounting cut-out:	Ø 22 mm
--------------------------	---------

OPERATING-/INDICATION PART

Illumination colour:	Blue
Lens shape:	flush
Lens optics:	opaque
Lens material:	Aluminium
Lens colour:	Nature
Lens illumination:	illuminative
Shape of illumination:	Ring

ELECTRICAL CHARACTERISTICS

Pollution degree:	2, according to EN IEC 60947-1
Electric strength:	1500 VAC, 50 Hz 1 minute between live terminals and ground
Electrical lifetime:	50 000 cycles of operation
Rated insulation voltage Ui:	250 V
Thermal current Ith:	5 A
Rated Operational Voltage Ue:	250 VAC

Contacts:	1 C		
Switching voltage and switching current:	according to IEC 60947-5-1 (Silver contacts) Service categorie AC-15		
Voltage	Current		
24 VAC	1 A		
35 VAC	1 A (M12 versio		
110 VAC	1 A		
220 VAC	0.5 A		
Switch rating DC service categorie DC-13 (Silver contacts)			
Voltage	Current		
24 VDC	0.7 A		
35 VDC	0.5 A (M12 vers		
110 VDC	0.2 A		
220 VDC	0.1 A		
according to UL 508 (Silver contacts) $\cos\phi$ 0,75 ... 0,8			
Voltage	Current		
120 VAC	5 A		
240 VAC	3 A		
24 VAC	1 A		
Operating voltage:	24 V AC/DC		

MECHANICAL CHARACTERISTIC

Tightening torque:	0.5 ... 0.6 Nm
Operating Travel:	ca. 3 mm
Contact material:	Silver
Switching system:	Snap-action switching element
Operating force:	4 N ... 7 N
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Switching action:	Maintained
Mechanical lifetime:	500 000 cycles of operation
Weight:	0.018 kg

AMBIENT CONDITION

Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27
Operating temperature:	- 30 °C ... + 70 °C
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Storage temperature:	- 40 °C ... + 80 °C
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

CERTIFICATE

Conformities:

CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

Approbations:

CB, CCC, C UL, UL

OTHER


Kind of illumination:

Single-LED


Short Description:

Illuminated pushbutton Ø 22 mm silver contact, Maintained, 24 V AC/DC, 1 C, Soldering terminal, 2.8 x 0.5 mm, Aluminium, Blue, Nature


Wiring diagrams:



Component layouts:



Dimension drawings:



A = Solder terminal
B = Screw terminal

Mounting cut-outs:

