

Illuminated pushbutton with connector M12, Ø 22 mm,
stainless steel 316L, Series 82, Ø 25 mm, flush, Silver, IP65,
IP67, Cable 200 mm, 180°

82-6655.1134



<https://eao.com/p/fb67666c>

Your product:



82-6655.1134

Illuminated pushbutton with connector
M12, Ø 22 mm, stainless steel 316L,
Series 82, Ø 25 mm, flush, Silver, IP65,
IP67, Cable 200 mm, 180°

PRODUCT RANGE

HMI function: Illuminated pushbutton

Series: Series 82

FRONT

Front dimension: Ø 25 mm

Front bezel colour: Silver

Front bezel material: Stainless steel 316L

MOUNTING

Design: flush

Mounting cut-out: Ø 22 mm

OPERATING-/INDICATION PART

Shape of illumination: Ring

Lens illumination: illuminative

Lens colour: Silver

Lens shape: flush

Lens material: Stainless steel 316L

Lens optics: opaque

Illumination colour: Green

ELECTRICAL CHARACTERISTICS

Electrical lifetime:	50 000 cycles of operation
Switching rating:	35 V AC/DC @ 0,5 A
Lumi. Intensity:	mcd
Operating voltage:	24 V AC/DC ± 10 %
Operation current:	7 mA

MECHANICAL CHARATERISTIC

Tightening torque:	0.5 ... 0.6 Nm
Terminal:	Cable 200 mm, 180°
Terminal lenght cable:	200
Contact material:	Silver
Switching action:	Momentary
Switching system:	Snap-action switching element
Total weight:	0.026 kg

AMBIENT CONDITION

IP front protection:	IP65, IP67
Operating temperature:	- 30 °C ... + 70 °C
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

OTHER

Housing colour:	Silver
Housing material:	Stainless steel
Housing size:	19 mm
Symbol:	no symbol
Article number:	82-6655.1134