

**KEMET Part Number: ALC70A151BB400**  
(A546CD151M400A)

ALC70, Aluminum Electrolytic, 150  $\mu$ F, 20%, 400 VDC, -40/+85°C



**General Information**

<b>Series:</b>	ALC70
<b>Dielectric:</b>	Aluminum Electrolytic
<b>Description:</b>	Snap-In, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Lead:</b>	2 Pin
<b>AEC-Q200:</b>	No
<b>Notes:</b>	Dimensions D And L Include Slewing.
<b>Shelf Life:</b>	156 Weeks

**Dimensions**

<b>D</b>	25mm +1mm
<b>L</b>	30mm +/-2mm
<b>S</b>	10mm +/-0.1mm
<b>LL</b>	6.3mm +/-1mm
<b>F</b>	2mm +/-0.1mm

**Packaging Specifications**

<b>Weight:</b>	28 g
<b>Slewing:</b>	Yes
<b>Packaging:</b>	Bulk, Bag

**Specifications**

<b>Capacitance:</b>	150 $\mu$ F
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	400 VDC, 440 VDC (Surge)
<b>Temperature Range:</b>	-40/+85°C
<b>Rated Temperature:</b>	85°C
<b>Life:</b>	10000 Hrs (Rated Voltage And Ripple Current At 85C), 16000 Hrs (Rated Voltage at 85C)
<b>Resistance:</b>	915 mOhms (100Hz 20C), 482 mOhms (10kHz 20C)
<b>Ripple Current:</b>	1.01 Amps (100Hz 85C), 2.46 Amps (10kHz 85C)
<b>Leakage Current:</b>	360 $\mu$ A (5min 20°C)