

KEMET Part Number: ALC70A471EB350
(A546HD471M350A)

ALC70, Aluminum Electrolytic, 470 uF, 20%, 350 VDC, -40/+85°C



| General Information | |
|---------------------|-------------------------------------|
| Series: | ALC70 |
| Dielectric: | Aluminum Electrolytic |
| Description: | Snap-In, Aluminum Electrolytic |
| RoHS: | Yes |
| Lead: | 2 Pin |
| AEC-Q200: | No |
| Notes: | Dimensions D And L Include Slewing. |
| Shelf Life: | 156 Weeks |

| Dimensions | |
|------------|---------------|
| D | 40mm +1mm |
| L | 30mm +/-2mm |
| S | 10mm +/-0.1mm |
| LL | 6.3mm +/-1mm |
| F | 2mm +/-0.1mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Weight: | 55 g |
| Slewing: | Yes |
| Packaging: | Bulk, Bag |

| Specifications | |
|------------------------|---|
| Capacitance: | 470 uF |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 350 VDC, 385 VDC (Surge) |
| Temperature Range: | -40/+85°C |
| Rated Temperature: | 85°C |
| Life: | 18000 Hrs (Rated Voltage And Ripple Current At 85C), 29000 Hrs (Rated Voltage at 85C) |
| Resistance: | 312 mOhms (100Hz 20C), 166 mOhms (10kHz 20C) |
| Ripple Current: | 2.29 Amps (100Hz 85C), 5 Amps (10kHz 85C) |
| Leakage Current: | 987 uA (5min 20°C) |