




BC9191-0100 | Building Automation Room Controller

Ethernet TCP/IP The compact BC9191 Room Controller has an integrated PLC and the sensor/actuator interfaces necessary for room automation. This way, it can be used as an autonomous or local controller. Compared with the BC9191-0000, the BC9191-0100 has an RS485 interface so that, for example, room control units, weather stations, electric door openers or DMX slaves can be connected. Communication with the devices generally takes place via the Modbus RTU protocol, but may also take place via a serial protocol which the user can freely define. The K-bus interface makes extension by the entire range of Bus Terminals possible at any time.

PLC data	Ethernet TCP/IP BC9191-0100
Programming	with TwinCAT via Ethernet
Program memory	128 kbytes
Data memory	128 kbytes
Remanent data	2 kbytes
Runtime system	1 PLC task
Programming languages	IEC 61131-3 (IL, LD, FBD, SFC, ST)
Online change	yes

Technical data	BC9191-0100
Number of Bus Terminals	64
Max. number of bytes fieldbus	512 byte input and 512 byte output
Ethernet interface	2 x RJ45 (switched)
Protocol	TwinCAT ADS, Modbus TCP
Digital inputs	3 contacts (e.g. window contact, dew point, occupancy sensor)
Analog inputs	3 x 0...10 V (e.g. CO ₂ sensor, air quality sensor, brightness sensor) 1 x Pt/Ni1000 (-20...+60 °C) for air temperature measurement 1 x resistance measurement for set value specification (0...10 KΩ)
Digital outputs	1 x 230 V AC, 10 A, relay (e.g. air heater) 3 x 230 V AC, 1 A, relay (3-stage fan) 2 x 230 V AC, 1 A, triac (e.g. valves for heating and cooling)
Analog outputs	2 x 0...10 V (e.g. volumetric air flow controller)
Bus interface	2 x RJ45 (switched)
Sub bus system	1 x RS485
Supply voltage	230 V AC
Current supply K-bus	200 mA
Dimensions (W x H x D)	118 mm (127 mm with end cap and DIN rail mounting) x 100 mm x 70 mm
Weight	approx. 345 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Protect. class/installation pos.	IP 20/vertical
Approvals	CE

Accessories	
KS2000	configuration software for extended parameterisation
TwinCAT PLC	programming system conforms to IEC 61131-3
Cordsets	cordsets and connectors
FC90xx-00xx	PC Fieldbus Cards with PCI interface
TS6255	IEC 61131-3 software library for TwinCAT PLC with Modbus RTU function blocks for serial communication with Modbus devices
System	
Ethernet TCP/IP	For further Ethernet TCP/IP products please see the system overview