

VERONICA-SQ-MINI-O

~15° + 50° oval beam


TECHNICAL SPECIFICATIONS:

Dimensions	13.9 mm
Height	8.9 mm
Fastening	tape, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	8.9 kg
Quantity in Box	5544 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
VERONICA-SQ-MINI-O	Single lens	PMMA	clear
VERONICA-SQ-MINI-TAPE	Tape	Acrylic foam	clear



LEDiL[®]



PRODUCT DATASHEET

CA14602_VERONICA-SQ-MINI-O



PHOTOMETRIC DATA (MEASURED):





LED XD16
FWHM 41.0 + 18.0°
Efficiency 89 %
Peak intensity 2.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-E2
FWHM 42.0 + 14.0°
Efficiency 92 %
Peak intensity 3.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G2
FWHM 45.0 + 20.0°
Efficiency 92 %
Peak intensity 2.300 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G3
FWHM 41.0 + 24.0°
Efficiency 92 %
Peak intensity 1.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LEDiL[®]



PRODUCT DATASHEET

CA14602_VERONICA-SQ-MINI-O



PHOTOMETRIC DATA (MEASURED):





LED LUXEON Rebel
FWHM 42.0 + 20.0°
Efficiency 90 %
Peak intensity 2.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON Rebel ES
FWHM 50.0 + 23.0°
Efficiency 80 %
Peak intensity 2.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON TX
FWHM 42.0 + 22.0°
Efficiency 90 %
Peak intensity 2.060 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NCSxE17A
FWHM 40.0 + 20.0°
Efficiency 89 %
Peak intensity 2.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED NVSxx19B/NVSxx19C
FWHM 41.0 + 23.0°
Efficiency 90 %
Peak intensity 1.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED Duris S5 (2 chip)
FWHM 76.0 + 22.0°
Efficiency 74 %
Peak intensity 1.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM Square EC
FWHM 42.0 + 20.0°
Efficiency 89 %
Peak intensity 2.150 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LH181A
FWHM 42.0 + 22.0°
Efficiency 88 %
Peak intensity 1.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED LH181B
FWHM 22.0 + 41.0°
Efficiency 91 %
Peak intensity 1.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Z8Y22P
FWHM 46.0 + 23.0°
Efficiency 90 %
Peak intensity 1.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LEDiL[®]


PRODUCT DATASHEET

CA14602_VERONICA-SQ-MINI-O


PHOTOMETRIC DATA (SIMULATED):




LED LUXEON C
FWHM 53.0 + 17.0°
Efficiency 87 %
Peak intensity 2.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Z ES
FWHM 53.0 + 16.0°
Efficiency 92 %
Peak intensity 2.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM Square CSSRM2/CSSRM3
FWHM 48.0 + 20.0°
Efficiency 81 %
Peak intensity 2.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED OSLOM SSL 150
FWHM 55.0 + 16.0°
Efficiency 89 %
Peak intensity 2.570 cd/lm
LEDs/each optic 1
Light colour Blue
Required components:



PHOTOMETRIC DATA (SIMULATED):


OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM 54.0 + 15.0°
Efficiency 90 %
Peak intensity 2.760 cd/lm
LEDs/each optic 1
Light colour Green
Required components:



OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM 53.0 + 16.0°
Efficiency 90 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour Red
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)