

Bus elements | chainflex® CFCLEAN8

36

20 million

Double strokes guaranteed

Min. 70mm

bend radius e-skin® flat

3m

travel distance e-skin® flat

- For heaviest duty applications in e-skin® flat
- PTFE foil wrap
- Shielded
- Highly abrasion-resistant
- PVC-free

Dynamic information

	Bend radius	e-skin® flat linear	minimum 70mm (further radii in preparation, please see data sheet)
		fixed	minimum 3 x d
	Temperature	e-skin® linear	-10°C up to +80°C
		fixed	-25°C up to +90°C (following DIN EN 50305)
	v max.	unsupported	2m/s
	a max.		40m/s²
	Travel distance		Short, very fast applications with small radii and restricted installation space in an e-skin® flat

Cable structure

	Conductor	Very finely stranded special conductors with especially soft and bending resistant design, made of bare copper wires.
	Core insulation	Mechanically high-quality FEP mixture.
	Core structure	According to bus specification.
	Core identification	According to bus specification. ► Product range table
	Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer film	Low-adhesion, extremely abrasion-resistant and highly flexible PTFE wrap, adapted to suit the requirements in e-skin® flat. Colour: White

Electrical information

	Nominal voltage	300/300V
	Testing voltage	2,000V

Properties and approvals

	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	UL verified	Certificate No. B129699: „igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“ See data sheet for details ► www.igus.eu/CFCLEAN8
	UL AWM	
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	Air Purity Class 1, material/stranded structure tested by IPA according to ISO 14644-14, test report IG 2107-1242 Following 2014/35/EU
	CE	
	UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Typical application areas

- For heaviest duty applications and especially small radii in cleanroom with e-skin® flat
- Especially for short, very fast applications with small radii and restricted installation space
- Indoor applications with e-skin® flat
- Semi-conductor/OLED manufacturing, medical cleanroom



chainflex® CFCLEAN are not cables in the sense of the normal standards for cables. Due to the absence of the outer jacket in CFCLEAN, which provides mechanical protection for cables, the use of chainflex® CFCLEAN is only permitted inside e-skin® flat.

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
Ethernet/CAT5e				
CFCLEAN8.045	(4x(2x0.14))C	5.5	34	47

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Part No.	Characteristic wave impedance approx. [Ω]	Core group	Colour code
Ethernet/CAT5e			
CFCLEAN8.045	100	4x(2x0.14)	white/blue, white/orange, white/green, white/brown

Guarantee

igus chainflex

36

up to 36 months guarantee

igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year