## **Technical data sheet**



Version: A/0

CG608M DisplayPort M to HDMI M - Support 4K@60HZ

#### [Product Picture]



### **[Product Description]**

Model	
CG608M	
Cable Length	
1.5m, 1.8m, 2m, 3m	
Interface	
Input: Display port Male, with IC	
Output: HDMI type A Male	
Bandwidth	
Up to 18Gbps	
Resolution	
4K@60Hz,2K@120Hz	
Audio	
Uncompressed digital 7.1, 5.1 or 2 channels.	
Material	
Conductor Material	Oxygen Free Copper
Shell Material	Aluminum alloy Metal case alloy+PVC molding
Connector Material	24K Gold Plated

#### [Features]

- Supports max 4K@60Hz resolution, (Backward supports4K@30Hz, 2K@120Hz, 1080P@120Hz);
- Audio & Video Sync Transmission: Supports both high-definition audio and video pass through from your DP computer to an HDMI input for video streaming or gaming;
- Designed with tinned copper and triple-layer shielding, Strong Anti-interference Capability;
- The aluminum shell, nylon braided cover and gold-plated connectors all ensure the superior durability under

www.vcom.com.hk

# **Technical data sheet**

### CG608M DisplayPort M to HDMI M - Support 4K@60HZ

the heavy usage and multiple plugging and unplugging;

Plug and play without driver dependent

### [Application Environment]

Compatible with laptops (HP ProBook EliteBook, Lenovo ThinkPad), desktop tower (HP, Dell optiplex/Precision/xps, Lenovo), graphics card (AMD, NVIDIA) and other devices with a DisplayPort.

### [Notice]

The cable is not a bi-directional cable - it can only convert signal from DisplayPort to HDMI.

www.vcom.com.hk