

ANTI FIRE




(B)

FEATURES

- ✓ Radial with microswitch for fireproof and smokeproof doors with fire resistance 60 min. (E1260).
- ✓ Strength up to 500kgs.
- ✓ Max micro switch load: AC (125V)-3A DC (30V)-2A.
- ✓ Reversible (left and right hand).
- ✓ Symmetrical.
- ✓ Height 79 mm., width 18,2 mm.
- ✓ Fail – secure (NC) and fail-safe (NO) models.
- ✓ Assembling screws distance 52,5 mm.
- ✓ Power supply: 12, 24, 48 V AC / DC.
- ✓ 24 hours working models.
- ✓ Low or very low power consumption.
- ✓ Working temperature for NO electric strikes is 60 ° C.
- ✓ Durability: grade C - 200,000 cycles.
- ✓ Category of use - grade 3 - suitable for public buildings.
- ✓ Certificate of Conformity acc. to EN 14846.

TECHNICAL DATA



Model		
Standard	Low consump.	NO
1860RF	1868RF	1861RF

Power supply (V)	12-24V AC/DC Standard	12-24V AC/DC Low consump. 12V	24-48V AC/DC Low consump. 24V	12V DC NO	24V DC NO
Tolerance (%)	± 5 %				
Continuous work	< 1 min.	100 % 12V DC <1 min. 12V AC <1 min. 24V AC/DC	100 % 24V DC <1 min. 24V AC <1 min. 48V AC/DC	100 %	100 %
Resistance (Ω)	20	40	140	40	140
Power consumption DC (mA)	12V / 600 24V / 1100	12V / 300 24V / 600	24V / 170 48V / 340	12V / 300 -	24V / 170 -
Power consumption AC (mA)	12V / 500 24V / 1000	12V / 250 24V / 510	24V / 150 48V / 300	-	-
Max preload DC (N)	10	10	10	10	10
Max preload AC (N)	90	90	90	-	-

Recommended front plates: CE 194RE-6RF, CE 194EA-6RF