

GVK busbar fork, 3-phase+N, L1 - L2 - L3 - N, shortenable version, end caps not included, 1 meter, 16 mm²

Part no. GVK-16/3P+N-4TE
EP-501074
EL Number 1604097
(Norway)

General specifications		
Product name		Eaton Moeller series busbar
Part no.		GVK-16/3P+N-4TE
EAN		9010653035183
Product Length/Depth		1016 millimetre
Product height		31.5 millimetre
Product width		21 millimetre
Product weight		0.789 kilogram
Certifications		CE
Product Tradename		None
Product Type		Busbar
Product Sub Type		None
Product Specification Details		
Color		Grey
Cross section		16 mm ²
EL number		1604097
Electric connection type		Fork
Features		Insulated Can be cut to size
Number of modular spacings		56
Number of phases		3
Number of poles		Four-pole
Pitch dimensions		17.8 mm
Rated conditional short-circuit current (I _q)		25 kA
Rated operating voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I _u)		80 A
Suitable for		Devices with N-busbar 14 devices

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss10.0.1-27-37-13-06 [ACN992011])		
Number of phases		3
Number of poles		4
Suitable for number of devices		14
Module width	mm	17.8
Cross section	mm ²	16
Length	mm	1016
Width in number of modular spacings		56
Rated permanent current I _u	A	80
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I _q	kA	25
Max. rated operation voltage U _e	V	415

Rated short-time withstand current Icw		kA	0
Suitable for devices with N-conductor			Yes
Suitable for devices with auxiliary switch			No
Colour			Grey