

# Spring-loaded test probe

## GKS-101 305 115 A 0800

Item GKS-101-0018



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology

### General data

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| Product group                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group              | Short/robust GKS                              |
| Series                         | GKS-101                                       |
| Grid                           | 1.91 mm [75 mil]                              |
| Contacting from                | Pad, Female connector                         |
| Magnetic                       | Yes                                           |
| Installation type              | Plug-in                                       |
| Quick-exchange system          | Yes                                           |
| Adjustable installation height | No                                            |
| Non-rotating                   | No                                            |
| Compatible receptacle(s)       | KS-101                                        |
| Min. temperature               | - 40 °C [- 104 °F]                            |
| Max. temperature               | + 80 °C [+ 176 °F]                            |
| RoHS-compliant                 | RoHS-3;6c                                     |

### Electrical data


|                                       |          |
|---------------------------------------|----------|
| Current load capacity / rated current | 4 A      |
| Typical resistance (Ri)               | <20 mOhm |

### Mechanical data

|                                |                   |
|--------------------------------|-------------------|
| Total length                   | 27.3 mm [1.07 in] |
| Barrel diameter                | 1 mm [.039 in]    |
| Maximum stroke                 | 5.3 mm [.208 in]  |
| Spring pre-load                | 0.27 N [.971 ozf] |
| Collar height                  | 00                |
| Spring force at working stroke | 0.8 N [2.87 ozf]  |
| Recommended working stroke     | 4 mm [.157 in]    |

### Tip style data

|                    |                               |
|--------------------|-------------------------------|
| Tip style          | 05 bullet-nosed (full radius) |
| Tip diameter       | 1.15 mm [.045 in]             |
| Tip style surface  | A gold                        |
| Tip style material | 3 CuBe                        |



# Spring-loaded test probe


## GKS-101 305 115 A 0800

Item GKS-101-0018



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 10/23 EN

Learn more about  
ICT/FCT Test probes



ingun.com