

# Spring-loaded test probe GKS-112 305 200 A 0807

Item GKS-112-1798





GO TO PRODUCT



**ingun**<sup>®</sup>

Partner for Future Technology

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture:  
The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available



1:1



## General data

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | Metric standard                               |
| Series:                         | GKS-112                                       |
| Grid:                           | 2.54 mm [100 mil]                             |
| Contacting from:                | Pad, Female connector                         |
| Magnetic:                       | Yes                                           |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes                                           |
| Adjustable installation height: | No                                            |
| Non-rotating:                   | No                                            |
| Compatible receptacle(s):       | KS-112                                        |
| Min. temperature:               | - 40 °C [- 104 °F]                            |
| Max. temperature:               | + 80 °C [+ 176 °F]                            |
| RoHS-compliant:                 | RoHS-3;6c                                     |

## Electrical data

|                                        |          |
|----------------------------------------|----------|
| Current load capacity / rated current: | 5 A      |
| Typical resistance (Ri):               | <20 mOhm |

## Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 37.3 mm [1.46 in] |
| Barrel diameter:                | 1.66 mm [.065 in] |
| Maximum stroke:                 | 5.3 mm [.208 in]  |
| Spring pre-load:                | 0.27 N [.971 ozf] |
| Collar height:                  | 07                |
| Spring force at working stroke: | 0.8 N [2.87 ozf]  |
| Recommended working stroke:     | 4 mm [.157 in]    |

## Tip style data

|                     |                               |
|---------------------|-------------------------------|
| Tip style:          | 05 bullet-nosed (full radius) |
| Tip diameter:       | 2 mm [.078 in]                |
| Tip style surface:  | A gold                        |
| Tip style material: | 3 CuBe                        |

# Spring-loaded test probe


## GKS-112 305 200 A 0807

Item GKS-112-1798



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 03/24\_GB

Learn more about  
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com