

# Spring-loaded test probe

## GKS-113 306 300 A 3002 M

Item GKS-113-0356





**ingun**<sup>®</sup>

Partner for Future Technology

- Screw-in test probes for applications with possible vibrations or unwanted side and axial forces (migration of the test probe out of the receptacle is reliably prevented)
- The screw-in test probe is securely installed in the KS using a torque screwdriver and bit tool. The required screw-in torque is applied via a square post on the receptacle.
- Stainless steel versions for temperatures from -100 °C up to +200 °C available

### INGUN SELECTION



#### General data

|                                 |                                  |
|---------------------------------|----------------------------------|
| Product group:                  | Screw-in test probe              |
| Sub-product group:              | Screw-in test probe              |
| Series:                         | GKS-113 M screw-in               |
| Grid:                           | 4 mm [157 mil]                   |
| Contacting from:                | Pin, Post, Flat contact          |
| Magnetic:                       | Yes                              |
| Installation type:              | Screw-in                         |
| Quick-exchange system:          | Yes                              |
| Adjustable installation height: | No                               |
| Non-rotating:                   | No                               |
| Screw-in torque:                | 10 - 20 cNm [.885 - 1.77 lbf·in] |
| Compatible receptacle(s):       | KS-113 M                         |
| Min. temperature:               | - 40 °C [- 104 °F]               |
| Max. temperature:               | + 80 °C [+ 176 °F]               |
| RoHS-compliant:                 | RoHS-3;6c                        |

#### Electrical data

|                                        |          |
|----------------------------------------|----------|
| Current load capacity / rated current: | 8 A      |
| Typical resistance (Ri):               | <30 mOhm |

#### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 28.3 mm [1.11 in] |
| Barrel diameter:                | 2.65 mm [.104 in] |
| Maximum stroke:                 | 5.3 mm [.208 in]  |
| Spring pre-load:                | 0.8 N [2.87 ozf]  |
| Collar height:                  | 02                |
| Spring force at working stroke: | 3 N [10.7 ozf]    |
| Recommended working stroke:     | 4 mm [.157 in]    |

SCREW-IN TEST PROBE

# Spring-loaded test probe

## GKS-113 306 300 A 3002 M

Item GKS-113-0356




**ingun**<sup>®</sup>

Partner for Future Technology

### Tip style data

|                     |                |
|---------------------|----------------|
| Tip style:          | 06 serrated    |
| Tip diameter:       | 3 mm [.118 in] |
| Tip style surface:  | A gold         |
| Tip style material: | 3 CuBe         |



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 04/24\_GB

Learn more about  
Screw-in test probe



SCREW-IN TEST PROBE

ingun.com