





GO TO PRODUCT

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture: The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available



1:1



### General data

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | Metric standard                               |
| Series:                         | GKS-113                                       |
| Grid:                           | 4 mm [157 mil]                                |
| Contacting from:                | Pad, Female connector                         |
| Magnetic:                       | Yes                                           |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes                                           |
| Adjustable installation height: | No                                            |
| Non-rotating:                   | No                                            |
| Compatible receptacle(s):       | KS-113, KS-113 23                             |
| Min. temperature:               | - 40 °C [- 104 °F]                            |
| Max. temperature:               | + 80 °C [+ 176 °F]                            |
| RoHS-compliant:                 | RoHS-3;6c                                     |

### Electrical data

|                                        |          |
|----------------------------------------|----------|
| Current load capacity / rated current: | 8 A      |
| Typical resistance (Ri):               | <30 mOhm |

### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 30.3 mm [1.19 in] |
| Barrel diameter:                | 2.65 mm [.104 in] |
| Maximum stroke:                 | 5.3 mm [.208 in]  |
| Spring pre-load:                | 0.75 N [2.69 ozf] |
| Collar height:                  | 05                |
| Spring force at working stroke: | 2.25 N [8.09 ozf] |
| Recommended working stroke:     | 4 mm [.157 in]    |

### Tip style data

|                     |                               |
|---------------------|-------------------------------|
| Tip style:          | 05 bullet-nosed (full radius) |
| Tip diameter:       | 2.3 mm [.090 in]              |
| Tip style surface:  | A gold                        |
| Tip style material: | 3 CuBe                        |

# Test Probe

## GKS-113 305 230 A 2205


Item GKS-113-0694



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 03/24\_GB

Learn more about  
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com